


CERTIFICATE OF TRANSMISSION BY FACSIMILE (37 CFR 1.8)			Docket No. L9289.01127
Applicant(s): Yasuyo MARUWAKA, et al.			
Serial No. 09/820,636	Filing Date March 30, 2001	Examiner Chi Ho A Lee	Group Art Unit 2663
Invention: RATE MATCHING CALCULATION METHOD AND RATE MATCHING APPARATUS			
OFFICIAL RECEIVED CENTRAL FAX CENTER JUN 01 2004			
I hereby certify that this <u>IDS and Fee, PTO-1449, 58 page reference</u> (Identify type of correspondence)			
is being facsimile transmitted to the United States Patent and Trademark Office (Fax. No. <u>703-872-9306</u>)			
on <u>June 1, 2004</u> (Date)			
<u>James E. Ledbetter</u> (Typed or Printed Name of Person Signing Certificate)  (Signature)			
Note: Each paper must have its own certificate of mailing.			

P18/REV01

OFFICIAL

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of

Inventors:

Y. MARUWAKA et al.

Art Unit: 2663

RECEIVED
CENTRAL FAX CENTER

Application No.:

09/820,636

Examiner: Chi Ho A Lee JUN 01 2004

Filed:

March 30, 2001

For:

RATE MATCHING CALCULATION METHOD AND RATE MATCHING
APPARATUSINFORMATION DISCLOSURE STATEMENT
AND FEE UNDER 37 CFR \$1.17 (P)

#14

Assistant Commissioner of Patents
Washington, DC 20231


Dear Sir:

Pursuant to Rules 56 and 97(c), Applicants hereby call the attention of the Patent Office to the reference listed on the attached Form PTO-1449.

Applicants present this reference so that the Patent Office may, in the first instance, determine any relevancy thereof to the presently claimed invention, see Beckman Instruments, Inc. v. Chemtronics, Inc., 439 F.2d 1369, 1380, 165 USPQ 355, 364 (5th Cir. 1970). Also see Patent Office Rules 104 and 106. Applicants respectfully request that this reference be expressly considered during the prosecution of this application and made of record herein and appear among the "References Cited" on any patent to issue herefrom.

The Commissioner of Patents and Trademarks is hereby authorized to charge any additional fee (or credit any overpayment) to Deposit Account No. 19-4375.

Respectfully submitted,

James E. Ledbetter
Registration No. 28,732

Date: June 1, 2004

JEL/app
ATTORNEY DOCKET NO. 19289.01127
STEVENS, DAVIS, MILLER & MOSHER, L.L.P.
1615 L STREET, NW, Suite 850
P.O. Box 34387
WASHINGTON, DC 20043-4387
Telephone: (202) 785-0100
Facsimile: (202) 408-5200

3G TS 25.212 v3.2.0 (2000-03)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
Multiplexing and channel coding (FDD)
(Release 1999)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organisational Partners and shall not be implemented.
This Specification is provided for future development work within 3GPP only. The Organisational Partners accept no liability for any use of this Specification.
Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organisational Partners' Publications Offices.

3GPP

Release 1999

13

3G TS 25.212 V3.2.0 (2000-03)

4.2.2 Transport block concatenation and code block segmentation

All transport blocks in a TTI are serially concatenated. If the number of bits in a TTI is larger than Z , the maximum size of a code block in question, then code block segmentation is performed after the concatenation of the transport blocks. The maximum size of the code blocks depends on whether convolutional coding, turbo coding or no coding is used for the TrCH.

4.2.2.1 Concatenation of transport blocks

The bits input to the transport block concatenation are denoted by $b_{im1}, b_{im2}, b_{im3}, \dots, b_{imB_i}$ where i is the TrCH number, m is the transport block number, and B_i is the number of bits in each block (including CRC). The number of transport blocks on TrCH i is denoted by M_i . The bits after concatenation are denoted by $x_{i1}, x_{i2}, x_{i3}, \dots, x_{iX_i}$, where i is the TrCH number and $X_i = M_i B_i$. They are defined by the following relations:

$$x_{ik} = b_{i1k} \quad k = 1, 2, \dots, B_i$$

$$x_{ik} = b_{i,2,(k-B_i)} \quad k = B_i + 1, B_i + 2, \dots, 2B_i$$

$$x_{ik} = b_{i,3,(k-2B_i)} \quad k = 2B_i + 1, 2B_i + 2, \dots, 3B_i$$

...

$$x_{ik} = b_{i,M_i,(k-(M_i-1)B_i)} \quad k = (M_i - 1)B_i + 1, (M_i - 1)B_i + 2, \dots, M_i B_i$$

4.2.2.2 Code block segmentation

Segmentation of the bit sequence from transport block concatenation is performed if $X_i > Z$. The code blocks after segmentation are of the same size. The number of code blocks on TrCH i is denoted by C_i . If the number of bits input to the segmentation, X_i , is not a multiple of C_i , filler bits are added to the beginning of the first block. The filler bits are transmitted and they are always set to 0. The maximum code block sizes are:

- convolutional coding: $Z = 504$;
- turbo coding: $Z = 5114$;
- no channel coding: $Z = \text{unlimited}$.

The bits output from code block segmentation are denoted by $o_{ir1}, o_{ir2}, o_{ir3}, \dots, o_{irK_i}$, where i is the TrCH number, r is the code block number, and K_i is the number of bits.

$$\text{Number of code blocks: } C_i = \lceil X_i / Z \rceil$$

Number of bits in each code block:

if $X_i < 40$ and Turbo coding is used, then

$$K_i = 40$$

else

$$K_i = \lceil X_i / C_i \rceil$$

end if

$$\text{Number of filler bits: } Y_i = C_i K_i - X_i$$

If $X_i \leq Z$, then

$$o_{ilk} = 0 \quad k = 1, 2, \dots, Y_i$$

3GPP

Release 1999

14

3G TS 25.212 V3.2.0 (2000-03)

$$o_{ik} = x_{i,(k-Y_i)} \quad k = Y_i+1, Y_i+2, \dots, K_i$$

end if

If $X_i > Z$, then

$$o_{ik} = 0 \quad k = 1, 2, \dots, Y_i$$

$$o_{ik} = x_{i,(k-Y_i)} \quad k = Y_i+1, Y_i+2, \dots, K_i$$

$$o_{i2k} = x_{i,(k+K_i-Y_i)} \quad k = 1, 2, \dots, K_i$$

$$o_{i3k} = x_{i,(k+2K_i-Y_i)} \quad k = 1, 2, \dots, K_i$$

...

$$o_{iC_i k} = x_{i,(k+(C_i-1)K_i-Y_i)} \quad k = 1, 2, \dots, K_i$$

end if

4.2.3 Channel coding

Code blocks are delivered to the channel coding block. They are denoted by $o_{ir1}, o_{ir2}, o_{ir3}, \dots, o_{irK_i}$, where i is the TrCH number, r is the code block number, and K_i is the number of bits in each code block. The number of code blocks on TrCH i is denoted by C_i . After encoding the bits are denoted by $y_{ir1}, y_{ir2}, y_{ir3}, \dots, y_{irY_i}$, where Y_i is the number of encoded bits. The relation between o_{irk} and y_{irk} and between K_i and Y_i is dependent on the channel coding scheme.

The following channel coding schemes can be applied to TrCHs:

- convolutional coding;
- turbo coding;
- no coding.

Usage of coding scheme and coding rate for the different types of TrCH is shown in table 1.

The values of Y_i in connection with each coding scheme:

- convolutional coding with rate 1/2: $Y_i = 2 * K_i + 16$; rate 1/3: $Y_i = 3 * K_i + 24$;
- turbo coding with rate 1/3: $Y_i = 3 * K_i + 12$;
- no coding: $Y_i = K_i$.

Table 1: Usage of channel coding scheme and coding rate

Type of TrCH	Coding scheme	Coding rate
BCH	Convolutional coding	1/2
PCH		
RACH		1/3, 1/2
CPCH, DCH, DSCH, FACH	Turbo coding	1/3
	No coding	

3GPP

Release 1999

16

3G TS 25.212 V3.2.0 (2000-03)

The initial value of the shift registers of the 8-state constituent encoders shall be all zeros when starting to encode the input bits.

Output from the Turbo coder is

$$x_1, z_1, z'_1, x_2, z_2, z'_2, \dots, x_K, z_K, z'_K,$$

where x_1, x_2, \dots, x_K are the bits input to the Turbo coder i.e. both first 8-state constituent encoder and Turbo code internal interleaver, and K is the number of bits, and z_1, z_2, \dots, z_K and z'_1, z'_2, \dots, z'_K are the bits output from first and second 8-state constituent encoders, respectively.

The bits output from Turbo code internal interleaver are denoted by x'_1, x'_2, \dots, x'_K , and these bits are to be input to the second 8-state constituent encoder.




Figure 4: Structure of rate 1/3 Turbo coder (dotted lines apply for trellis termination only)

4.2.3.2.2 Trellis termination for Turbo coder

Trellis termination is performed by taking the tail bits from the shift register feedback after all information bits are encoded. Tail bits are padded after the encoding of information bits.

The first three tail bits shall be used to terminate the first constituent encoder (upper switch of figure 4 in lower position) while the second constituent encoder is disabled. The last three tail bits shall be used to terminate the second constituent encoder (lower switch of figure 4 in lower position) while the first constituent encoder is disabled.

The transmitted bits for trellis termination shall then be:

$$x_{K+1}, z_{K+1}, x_{K+2}, z_{K+2}, x_{K+3}, z_{K+3}, x'_{K+1}, z'_{K+1}, x'_{K+2}, z'_{K+2}, x'_{K+3}, z'_{K+3}.$$

4.2.3.2.3 Turbo code internal interleaver

The Turbo code internal interleaver consists of bits-input to a rectangular matrix, intra-row and inter-row permutations of the rectangular matrix, and bits-output from the rectangular matrix with pruning. The bits input to the Turbo code internal interleaver are denoted by $x_1, x_2, x_3, \dots, x_K$, where K is the integer number of the bits and takes one value of $40 \leq K \leq 5114$. The relation between the bits input to the Turbo code internal interleaver and the bits input to the channel coding is defined by $x_k = o_{irk}$ and $K = K_i$.

The following subclause specific symbols are used in subclauses 4.2.3.2.3.1 to 4.2.3.2.3.3:

- K Number of bits input to Turbo code internal interleaver
- R Number of rows of rectangular matrix

3GPP

Release 1999

17

3G TS 25.212 V3.2.0 (2000-03)

C	Number of columns of rectangular matrix
p	Prime number
v	Primitive root
s(i)	Base sequence for intra-row permutation
qj	Minimum prime integers
rj	Permuted prime integers
T(j)	Inter-row permutation pattern
Uj(i)	Intra-row permutation pattern
i	Index of matrix
j	Index of matrix
k	Index of bit sequence

4.2.3.2.3.1 Bits-input to rectangular matrix

The bit sequence input to the Turbo code internal interleaver x_k is written into the rectangular matrix as follows.

(1) Determine the number of rows R of the rectangular matrix such that:

$$R = \begin{cases} 5, & \text{if } (40 \leq K \leq 159) \\ 10, & \text{if } ((160 \leq K \leq 200) \text{ or } (481 \leq K \leq 530)) \\ 20, & \text{if } (K = \text{any other value}) \end{cases}$$

where the rows of rectangular matrix are numbered 0, 1, 2, ..., $R - 1$ from top to bottom.

(2) Determine the number of columns C of rectangular matrix such that:

if $(481 \leq K \leq 530)$ then

$$p = 53 \text{ and } C = p.$$

else

Find minimum prime p such that

$$(p + 1) - K/R \geq 0,$$

and determine C such that

if $(p - K/R \geq 0)$ then

if $(p - 1 - K/R \geq 0)$ then

$$C = p - 1.$$

else

$$C = p.$$

end if

else

$$C = p + 1$$

end if

3GPP

Release 1999

18

3G TS 25.212 V3.2.0 (2000-03)

end if

where the columns of rectangular matrix are numbered 0, 1, 2, ..., C - 1 from left to right.

- (3) Write the input bit sequence x_i into the $R \times C$ rectangular matrix row by row starting with bit x_1 in column 0 of row 0:

$$\begin{bmatrix} x_1 & x_2 & x_3 & \dots & x_C \\ x_{(C+1)} & x_{(C+2)} & x_{(C+3)} & \dots & x_{2C} \\ \vdots & \vdots & \vdots & \dots & \vdots \\ x_{((R-1)C+1)} & x_{((R-1)C+2)} & x_{((R-1)C+3)} & \dots & x_{RC} \end{bmatrix}$$

4.2.3.2.3.2 Intra-row and inter-row permutations

After the bits-input to the $R \times C$ rectangular matrix, the intra-row and inter-row permutations are performed by using the following algorithm.

- (1) Select a primitive root v from table 2.

- (2) Construct the base sequence $s(i)$ for intra-row permutation as:

$$s(i) = [v \times s(i-1)] \bmod p, \quad i = 1, 2, \dots, (p-2), \text{ and } s(0) = 1.$$

- (3) Let $q_0 = 1$ be the first prime integer in $\{q_j\}$, and select the consecutive minimum prime integers $\{q_j\}$ ($j = 1, 2, \dots, R-1$) such that:

$$\text{g.c.d}\{q_j, p-1\} = 1, \quad q_j > 6, \text{ and } q_j > q_{(j-1)},$$

where g.c.d. is greatest common divisor.

- (4) Permute $\{q_j\}$ to make $\{r_j\}$ such that

$$r_{T(j)} = q_j, \quad j = 0, 1, \dots, R-1,$$

where $T(j)$ indicates the original row position of the j -th permuted row, and $T(j)$ is the inter-row permutation pattern defined as the one of the following four kind of patterns: Pat_1 , Pat_2 , Pat_3 and Pat_4 depending on the number of input bits K .

$$T(j) = \begin{cases} Pat_4 & \text{if } (40 \leq K \leq 159) \\ Pat_3 & \text{if } (160 \leq K \leq 200) \\ Pat_1 & \text{if } (201 \leq K \leq 480) \\ Pat_3 & \text{if } (481 \leq K \leq 530) \\ Pat_1 & \text{if } (531 \leq K \leq 2280) \\ Pat_2 & \text{if } (2281 \leq K \leq 2480) \\ Pat_1 & \text{if } (2481 \leq K \leq 3160) \\ Pat_2 & \text{if } (3161 \leq K \leq 3210) \\ Pat_1 & \text{if } (3211 \leq K \leq 5114) \end{cases}$$

where Pat_1 , Pat_2 , Pat_3 and Pat_4 have the following patterns respectively.

$$Pat_1: \{19, 9, 14, 4, 0, 2, 5, 7, 12, 18, 10, 8, 13, 17, 3, 1, 16, 6, 15, 11\}$$

$$Pat_2: \{19, 9, 14, 4, 0, 2, 5, 7, 12, 18, 16, 13, 17, 15, 3, 1, 6, 11, 8, 10\}$$

$$Pat_3: \{9, 8, 7, 6, 5, 4, 3, 2, 1, 0\}$$

$$Pat_4: \{4, 3, 2, 1, 0\}$$

3GPP

Release 1999

19

3G TS 25.212 V3.2.0 (2000-03)

(5) Perform the j -th ($j = 0, 1, 2, \dots, R - 1$) intra-row permutation as:

if ($C = p$) then

$$U_j(i) = s([i \times r_j] \bmod (p - 1)), \quad i = 0, 1, 2, \dots, (p - 2), \text{ and } U_j(p - 1) = 0,$$

where $U_j(i)$ is the input bit position of i -th output after the permutation of j -th row.

end if

if ($C = p + 1$) then

$$U_j(i) = s([i \times r_j] \bmod (p - 1)), \quad i = 0, 1, 2, \dots, (p - 2), \quad U_j(p - 1) = 0, \text{ and } U_j(p) = p,$$

where $U_j(i)$ is the input bit position of i -th output after the permutation of j -th row, and

if ($K = C \times R$) then

Exchange $U_{R-1}(p)$ with $U_{R-1}(0)$.

end if

end if

if ($C = p - 1$) then

$$U_j(i) = s([i \times r_j] \bmod (p - 1)) - 1, \quad i = 0, 1, 2, \dots, (p - 2),$$

where $U_j(i)$ is the input bit position of i -th output after the permutation of j -th row.

end if

Table 2: Table of prime p and associated primitive root v

p	v	p	v	p	v	p	v	p	v
7	3	47	5	101	2	157	5	223	3
11	2	53	2	103	5	163	2	227	2
13	2	59	2	107	2	167	5	229	6
17	3	61	2	109	6	173	2	233	3
19	2	67	2	113	3	179	2	239	7
23	5	71	7	127	3	181	2	241	7
29	2	73	5	131	2	191	19	251	6
31	3	79	3	137	3	193	5	257	3
37	2	83	2	139	2	197	2		
41	6	89	3	149	2	199	3		
43	3	97	5	151	6	211	2		

4.2.3.2.3.3 Bits-output from rectangular matrix with pruning

After intra-row and inter-row permutations, the bits of the permuted rectangular matrix are denoted by y'_i :

$$\begin{bmatrix} y'_1 & y'_{(R+1)} & y'_{(2R+1)} & \dots & y'_{((C-1)R+1)} \\ y'_2 & y'_{(R+2)} & y'_{(2R+2)} & \dots & y'_{((C-1)R+2)} \\ \vdots & \vdots & \vdots & \dots & \vdots \\ y'_R & y'_{2R} & y'_{3R} & \dots & y'_{CR} \end{bmatrix}$$

3GPP

Release 1999

20

3G TS 25.212 V3.2.0 (2000-03)

The output of the Turbo code internal interleaver is the bit sequence read out column by column from the intra-row and inter-row permuted $R \times C$ matrix starting with bit y'_1 in row 0 of column 0 and ending with bit y'_{CR} in row $R - 1$ of column $C - 1$. The output is pruned by deleting bits that were not present in the input bit sequence, i.e. bits y'_k that corresponds to bits x_k with $k > K$ are removed from the output. The bits output from Turbo code internal interleaver are denoted by x'_1, x'_2, \dots, x'_K , where x'_1 corresponds to the bit y'_k with smallest index k after pruning, x'_2 to the bit y'_k with second smallest index k after pruning, and so on. The number of bits output from Turbo code internal interleaver is K and the total number of pruned bits is:

$$R \times C - K.$$

4.2.3.3 Concatenation of encoded blocks

After the channel coding for each code block, if C_i is greater than 1, the encoded blocks are serially concatenated so that the block with lowest index r is output first from the channel coding block, otherwise the encoded block is output from channel coding block as it is. The bits output are denoted by $c_{i1}, c_{i2}, c_{i3}, \dots, c_{iE_i}$, where i is the TrCH number and $E_i = C_i Y_i$. The output bits are defined by the following relations:

$$c_{ik} = y_{1k} \quad k = 1, 2, \dots, Y_i$$

$$c_{ik} = y_{1,2,(k-Y_i)} \quad k = Y_i + 1, Y_i + 2, \dots, 2Y_i$$

$$c_{ik} = y_{1,3,(k-2Y_i)} \quad k = 2Y_i + 1, 2Y_i + 2, \dots, 3Y_i$$

...

$$c_{ik} = y_{1,C_i,(k-(C_i-1)Y_i)} \quad k = (C_i - 1)Y_i + 1, (C_i - 1)Y_i + 2, \dots, C_i Y_i$$

If no code blocks are input to the channel coding ($C_i = 0$), no bits shall be output from the channel coding, i.e. $E_i = 0$.

4.2.4 Radio frame size equalisation

Radio frame size equalisation is padding the input bit sequence in order to ensure that the output can be segmented in F_i data segments of same size as described in subclause 4.2.7. Radio frame size equalisation is only performed in the UL (DL rate matching output block length is always an integer multiple of F_i).

The input bit sequence to the radio frame size equalisation is denoted by $c_{i1}, c_{i2}, c_{i3}, \dots, c_{iE_i}$, where i is TrCH number and E_i the number of bits. The output bit sequence is denoted by $t_{i1}, t_{i2}, t_{i3}, \dots, t_{iT_i}$, where T_i is the number of bits. The output bit sequence is derived as follows:

- $t_{ik} = c_{ik}$, for $k = 1 \dots E_i$; and
- $t_{ik} = \{0, 1\}$ for $k = E_i + 1 \dots T_i$, if $E_i < T_i$

where

- $T_i = F_i * N_i$; and
- $N_i = \lceil E_i / F_i \rceil$ is the number of bits per segment after size equalisation.

4.2.5 1st interleaving

In Compressed Mode by puncturing, bits marked with a fourth value on top of $\{0, 1, \delta\}$ and noted p, are introduced in the radio frames to be compressed, in positions corresponding to the first bits of the radio frames. They will be removed in a later stage of the multiplexing chain to create the actual gap. Additional puncturing has been performed in the rate matching step, over the TTI containing the compressed radio frame, to create room for these p-bits. The following subclause describes this feature.

Release 1999

21

3G TS 25.212 V3.2.0 (2000-03)

4.2.5.1 Insertion of marked bits in the sequence to be input in first interleaver

In normal mode, compressed mode by higher layer scheduling, and compressed mode by spreading factor reduction:

$$x_{ik} = z_{ik} \text{ and } X_i = Z_i.$$

In case of compressed mode by puncturing and fixed positions, sequence $x_{i,k}$ which will be input to first interleaver for TrCh i and TTI m within largest TTI, is built from bits $z_{i,k}$, $k=1, \dots, Z_i$, plus $Np^{TTI,m}_{i,max}$ bits marked p and $X_i = Z_i + Np^{TTI,m}_{i,max}$, as is described thereafter.

$Np^{TTI,m}_{i,max}$ is defined in the Rate Matching subclause 4.2.7.

$P_{Fi}[x]$ defines the inter column permutation function for a TTI of length $F_i * 10\text{ms}$, as defined in Table 3 above. $P_{Fi}[x]$ is the Bit Reversal function of x on $\log_2(F_i)$ bits.

NOTE 1: $C[x]$, $x=0$ to F_i-1 , the number of bits p which have to be inserted in each of the F_i segments of the TTI, i.e. in each column of the first interleaver. $C[x]$ is equal to $Np^x_{i,max}$ for x equal 0 to F_i-1 for fixed positions. It is noted $Np^x_{i,max}$ in the following initialisation step.

NOTE 2: $cbi[x]$, $x=0$ to F_i-1 , the counter of the number of bits p inserted in each of the F_i segments of the TTI, i.e. in each column of the first interleaver.

col = 0

while col < F_i do

$C[\text{col}] = Np^{\text{col}}_{i,max}$ -- initialisation of number of bits p to be inserted in each of the F_i segments of the TTI

$cbi[\text{col}] = 0$ -- initialisation of counter of number of bits p inserted in each of the F_i segments of the TTI

end do

$n = 0$, $m = 0$

while $n < X_i$ do

col = $n \bmod F_i$

if $cbi[\text{col}] < C[P_{Fi}(\text{col})]$ do

$x_{i,n} = p$ -- insert one p bit

$cbi[\text{col}] = cbi[\text{col}] + 1$ -- update counter of number of bits p inserted

else -- no more p bit to insert in this segment

$x_{i,n} = z_{i,m}$

$m = m + 1$

endif

$n = n + 1$

end do

4.2.5.2 1st interleaver operation

The 1st interleaving is a block interleaver with inter-column permutations. The input bit sequence to the 1st interleaver is denoted by $x_{i1}, x_{i2}, x_{i3}, \dots, x_{iX_i}$, where i is TrCH number and X_i the number of bits (at this stage X_i is assumed and guaranteed to be an integer multiple of TTI). The output bit sequence is derived as follows:

(1) Select the number of columns C_i from table 3.

3GPP

Release 1999

22

3G TS 25.212 V3.2.0 (2000-03)

(2) Determine the number of rows R_i defined as:

$$R_i = X_i / C_i$$

(3) Write the input bit sequence into the $R_i \times C_i$ rectangular matrix row by row starting with bit $x_{i,1}$ in the first column of the first row and ending with bit $x_{i,(R_i C_i)}$ in column C_i of row R_i :

$$\begin{bmatrix} x_{i1} & x_{i2} & x_{i3} & \dots & x_{iC_i} \\ x_{i,(C_i+1)} & x_{i,(C_i+2)} & x_{i,(C_i+3)} & \dots & x_{i,(2C_i)} \\ \vdots & \vdots & \vdots & \dots & \vdots \\ x_{i,((R_i-1)C_i+1)} & x_{i,((R_i-1)C_i+2)} & x_{i,((R_i-1)C_i+3)} & \dots & x_{i,(R_i C_i)} \end{bmatrix}$$

(4) Perform the inter-column permutation based on the pattern $\{P_i(j)\}$ ($j=0,1,\dots,C_i-1$) shown in table 3, where $P_i(j)$ is the original column position of the j -th permuted column. After permutation of the columns, the bits are denoted by y_{ik} :

$$\begin{bmatrix} y_{i1} & y_{i,(R_i+1)} & y_{i,(2R_i+1)} & \dots & y_{i,((C_i-1)R_i+1)} \\ y_{i2} & y_{i,(R_i+2)} & y_{i,(2R_i+2)} & \dots & y_{i,((C_i-1)R_i+2)} \\ \vdots & \vdots & \vdots & \dots & \vdots \\ y_{iR_i} & y_{i,(2R_i)} & y_{i,(3R_i)} & \dots & y_{i,(C_i R_i)} \end{bmatrix}$$

(5) Read the output bit sequence $y_{i1}, y_{i2}, y_{i3}, \dots, y_{i,(R_i C_i)}$ of the 1st interleaving column by column from the inter-column permuted $R_i \times C_i$ matrix. Bit $y_{i,1}$ corresponds to the first row of the first column and bit $y_{i,(R_i C_i)}$ corresponds to row R_i of column C_i .

Table 3

TTI	Number of columns C_i	Inter-column permutation patterns
10 ms	1	{0}
20 ms	2	{0,1}
40 ms	4	{0,2,1,3}
80 ms	8	{0,4,2,6,1,5,3,7}

4.2.5.3 Relation between input and output of 1st interleaving in uplink

The bits input to the 1st interleaving are denoted by $t_{i1}, t_{i2}, t_{i3}, \dots, t_{iT_i}$, where i is the TrCH number and T_i the number of bits. Hence, $z_{ik} = t_{ik}$ and $X_i = T_i$.

The bits output from the 1st interleaving are denoted by $d_{i1}, d_{i2}, d_{i3}, \dots, d_{iT_i}$, and $d_{ik} = y_{ik}$.

4.2.5.4 Relation between input and output of 1st interleaving in downlink

If fixed positions of the TrCHs in a radio frame is used then the bits input to the 1st interleaving are denoted by $h_{i1}, h_{i2}, h_{i3}, \dots, h_{i(F_i H_i)}$, where i is the TrCH number. Hence, $z_{ik} = h_{ik}$ and $Z_i = F_i * H_i - Np^{TTI, n_{i, max}}$ in compressed mode by puncturing, and $Z_i = F_i H_i$ otherwise.

If flexible positions of the TrCHs in a radio frame is used then the bits input to the 1st interleaving are denoted by $g_{i1}, g_{i2}, g_{i3}, \dots, g_{iG_i}$, where i is the TrCH number. Hence, $z_{ik} = g_{ik}$ and $Z_i = G_i$.

The bits output from the 1st interleaving are denoted by $q_{i1}, q_{i2}, q_{i3}, \dots, q_{iQ_i}$, where i is the TrCH number and Q_i is the number of bits. Hence, $q_{ik} = y_{ik}$, $Q_i = F_i H_i$ if fixed positions are used, and $Q_i = G_i$ if flexible positions are used.

3GPP

Release 1999

23

3G TS 25.212 V3.2.0 (2000-03)

4.2.6 Radio frame segmentation

When the transmission time interval is longer than 10 ms, the input bit sequence is segmented and mapped onto consecutive F_i radio frames. Following rate matching in the DL and radio frame size equalisation in the UL the input bit sequence length is guaranteed to be an integer multiple of F_i .

The input bit sequence is denoted by $x_{i1}, x_{i2}, x_{i3}, \dots, x_{iX_i}$, where i is the TrCH number and X_i is the number bits. The F_i output bit sequences per TTI are denoted by $y_{i,n_1}, y_{i,n_2}, y_{i,n_3}, \dots, y_{i,n_{Y_i}}$ where n_i is the radio frame number in current TTI and Y_i is the number of bits per radio frame for TrCH i . The output sequences are defined as follows:

$$y_{i,n,k} = x_{i,((n-1)Y_i)+k}, n_i = 1 \dots F_i, k = 1 \dots Y_i$$

where

$Y_i = (X_i / F_i)$ is the number of bits per segment.

The n_i -th segment is mapped to the n_i -th radio frame of the transmission time interval.

4.2.6.1 Relation between input and output of the radio frame segmentation block in uplink

The input bit sequence to the radio frame segmentation is denoted by $d_{i1}, d_{i2}, d_{iT_i}, \dots, d_{iT_i}$, where i is the TrCH number and T_i the number of bits. Hence, $x_{ik} = d_{ik}$ and $X_i = T_i$.

The output bit sequence corresponding to radio frame n_i is denoted by $e_{i1}, e_{i2}, e_{i3}, \dots, e_{iN_i}$, where i is the TrCH number and N_i is the number of bits. Hence, $e_{i,k} = y_{i,n,k}$ and $N_i = Y_i$.

4.2.6.2 Relation between input and output of the radio frame segmentation block in downlink

The bits input to the radio frame segmentation are denoted by $q_{i1}, q_{i2}, q_{i3}, \dots, q_{iQ_i}$, where i is the TrCH number and Q_i the number of bits. Hence, $x_{ik} = q_{ik}$ and $X_i = Q_i$.

The output bit sequence corresponding to radio frame n_i is denoted by $f_{i1}, f_{i2}, f_{i3}, \dots, f_{iV_i}$, where i is the TrCH number and V_i is the number of bits. Hence, $f_{i,k} = y_{i,n,k}$ and $V_i = Y_i$.

4.2.7 Rate matching

Rate matching means that bits on a transport channel are repeated or punctured. Higher layers assign a rate-matching attribute for each transport channel. This attribute is semi-static and can only be changed through higher layer signalling. The rate-matching attribute is used when the number of bits to be repeated or punctured is calculated.

The number of bits on a transport channel can vary between different transmission time intervals. In the downlink the transmission is interrupted if the number of bits is lower than maximum. When the number of bits between different transmission time intervals in uplink is changed, bits are repeated or punctured to ensure that the total bit rate after TrCH multiplexing is identical to the total channel bit rate of the allocated dedicated physical channels.

If no bits are input to the rate matching for all TrCHs within a CCTrCH, the rate matching shall output no bits for all TrCHs within the CCTrCH and no uplink DPDCH will be selected in the case of uplink rate matching.

Notation used in subclause 4.2.7 and subclauses:

N_{ij} : For uplink: Number of bits in a radio frame before rate matching on TrCH i with transport format combination j .

For downlink: An intermediate calculation variable (not an integer but a multiple of 1/8).

Release 1999

24

3G TS 25.212 V3.2.0 (2000-03)

- N_{it}^{TTI} : Number of bits in a transmission time interval before rate matching on TrCH i with transport format l .
Used in downlink only.
- ΔN_{ij} : For uplink: If positive - number of bits that should be repeated in each radio frame on TrCH i with transport format combination j .
If negative - number of bits that should be punctured in each radio frame on TrCH i with transport format combination j .
For downlink: An intermediate calculation variable (not an integer but a multiple of 1/8).
- ΔN_{it}^{TTI} : If positive - number of bits to be repeated in each transmission time interval on TrCH i with transport format j .
If negative - number of bits to be punctured in each transmission time interval on TrCH i with transport format j .
Used in downlink only.
- $N_p^{TTI, m}$, $m=0$ to $F_i - 1$: Positive or null: number of bits to be removed in TTI number m within the largest TTI, to create the required gaps in the compressed radio frames of this TTI, in case of compressed mode by puncturing, for TrCH i with transport format l . In case of fixed positions and compressed mode by puncturing, this value is noted $N_p^{TTI, m}$, l, max since it is calculated for all TrCh with their maximum number of bits; thus it is the same for all TFCs
Used in downlink only.
- $N_p^{n, l}$, $n=0$ to $F_{max} - 1$: Positive or null: number of bits, in radio frame number n within the largest TTI, corresponding to the gap for compressed mode in this radio frame, for TrCH i with transport format l . The value will be null for the un-compressed radio frames. In case of fixed positions and compressed mode by puncturing, this value is noted $N_p^{n, l, max}$ since it is calculated for all TrChs with their maximum number of bits; thus it is the same for all TFCs
Used in downlink only.
- $N_{TGL}[k]$, $k=0$ to $F_i - 1$: Positive or null: number of bits in each radio frame corresponding to the gap for compressed mode for the CCTrCh.
- RM_i : Semi-static rate matching attribute for transport channel i . Signalled from higher layers.
- PL : Puncturing limit for uplink. This value limits the amount of puncturing that can be applied in order to avoid multicode or to enable the use of a higher spreading factor. Signalled from higher layers.
- $N_{data, j}$: Total number of bits that are available for the CCTrCH in a radio frame with transport format combination j .
- I : Number of TrCHs in the CCTrCH.
- Z_{ij} : Intermediate calculation variable.
- F_i : Number of radio frames in the transmission time interval of TrCH i .
- F_{max} : Maximum number of radio frames in a transmission time interval used in the CCTrCH :

$$F_{max} = \max_{1 \leq i \leq I} F_i$$
- n_i : Radio frame number in the transmission time interval of TrCH i ($0 \leq n_i < F_i$).
- q : Average puncturing or repetition distance (normalised to only show the remaining rate matching on top of an integer number of repetitions). Used in uplink only.
- $I_i(n_i)$: The inverse interleaving function of the 1st interleaver (note that the inverse interleaving function is identical to the interleaving function itself for the 1st interleaver). Used in uplink only.

3GPP

Release 1999

25

3G TS 25.212 V3.2.0 (2000-03)

- $S(n)$: The shift of the puncturing or repetition pattern for radio frame n . Used in uplink only.
- $TF_i(j)$: Transport format of TrCH i for the transport format combination j .
- $TFS(i)$: The set of transport format indexes i for TrCH i .
- $TFCS$: The set of transport format combination indexes j .
- e_{int} : Initial value of variable e in the rate matching pattern determination algorithm of subclause 4.2.7.5.
- e_{plus} : Increment of variable e in the rate matching pattern determination algorithm of subclause 4.2.7.5.
- e_{minus} : Decrement of variable e in the rate matching pattern determination algorithm of subclause 4.2.7.5.
- b : Indicates systematic and parity bits
- $b=1$: Systematic bit. $X(i)$ in subclause 4.2.3.2.1.
- $b=2$: 1st parity bit (from the upper Turbo constituent encoder). $Y(i)$ in subclause 4.2.3.2.1.
- $b=3$: 2nd parity bit (from the lower Turbo constituent encoder). $Y'(i)$ in subclause 4.2.3.2.1.

The * (star) notation is used to replace an index x when the indexed variable X_x does not depend on the index x . In the left wing of an assignment the meaning is that " $X_* = Y$ " is equivalent to "for all x do $X_x = Y$ ". In the right wing of an assignment, the meaning is that " $Y = X_*$ " is equivalent to "take any x and do $Y = X_x$ ".

The following relations, defined for all TFC j , are used when calculating the rate matching parameters:

$$Z_{0,j} = 0$$

$$Z_{ij} = \left\lfloor \frac{\left(\sum_{m=1}^I RM_m \cdot N_{mj} \right) \cdot N_{data,j}}{\sum_{m=1}^I RM_m \cdot N_{mj}} \right\rfloor \quad \text{for all } i = 1 \dots I \quad (1)$$

$$\Delta N_{ij} = Z_{ij} - Z_{i-1,j} - N_{ij} \quad \text{for all } i = 1 \dots I$$

4.2.7.1 Determination of rate matching parameters in uplink

4.2.7.1.1 Determination of SF and number of PhCHs needed

In uplink, puncturing can be applied to match the CCTrCH bit rate to the PhCH bit rate. The bit rate of the PhCH(s) is limited by the UE capability and restrictions imposed by UTRAN, through limitations on the PhCH spreading factor. The maximum amount of puncturing that can be applied is signalled from higher layers and denoted by PL . The number of available bits in the radio frames of one PhCH for all possible spreading factors is given in [2]. Denote these values by $N_{256}, N_{128}, N_{64}, N_{32}, N_{16}, N_8$, and N_4 , where the index refers to the spreading factor. The possible number of bits available to the CCTrCH on all PhCHs, N_{data} , then are $\{N_{256}, N_{128}, N_{64}, N_{32}, N_{16}, N_8, N_4, 2N_4, 3N_4, 4N_4, 5N_4, 6N_4\}$. Depending on the UE capability and the restrictions from UTRAN, the allowed set of N_{data} , denoted SET0, can be a subset of $\{N_{256}, N_{128}, N_{64}, N_{32}, N_{16}, N_8, N_4, 2N_4, 3N_4, 4N_4, 5N_4, 6N_4\}$. $N_{data,j}$ for the transport format combination j is determined by executing the following algorithm:

$$SET1 = \{ N_{data} \text{ in SET0 such that } \min_{1 \leq y \leq I} \{ RM_y \} \cdot N_{data} - \sum_{x=1}^I RM_x \cdot N_{x,j} \text{ is non negative} \}$$

If SET1 is not empty and the smallest element of SET1 requires just one PhCH then

$$N_{data,j} = \min SET1$$

else

Release 1999

26

3G TS 25.212 V3.2.0 (2000-03)

SET2 = { N_{data} in SET0 such that $\min_{1 \leq y \leq I} \{RM_y\} \cdot N_{data} - PL \cdot \sum_{x=1}^I RM_x \cdot N_{x,j}$ is non negative }

Sort SET2 in ascending order

$N_{data} = \min \text{ SET2}$

While N_{data} is not the max of SET2 and the follower of N_{data} requires no additional PhCH do

$N_{data} = \text{follower of } N_{data} \text{ in SET2}$

End while

$N_{data,j} = N_{data}$

End if

4.2.7.1.2 Determination of parameters needed for calculating the rate matching pattern

The number of bits to be repeated or punctured, ΔN_{ij} , within one radio frame for each TrCH i is calculated with equation 1 for all possible transport format combinations j and selected every radio frame. $N_{data,j}$ is given from subclause 4.2.7.1.1.

In compressed mode $N_{data,j}$ is replaced by $N_{data,j}^{cm}$ in Equation 1. $N_{data,j}^{cm}$ is given as follows:

In compressed mode by higher layer scheduling, $N_{data,j}^{cm}$ is obtained by executing the algorithm in subclause 4.2.7.1.1

but with the number of bits in one radio frame of one PhCH reduced to $\frac{N_{tr}}{15}$ of the value in normal mode.

N_{tr} is the number of transmitted slots in a compressed radio frame and is defined by the following relation:

$$N_{tr} = \begin{cases} 15 - TGL, & \text{if } N_{first} + TGL \leq 15 \\ N_{first}, & \text{in first frame if } N_{first} + TGL > 15 \\ 30 - TGL - N_{first}, & \text{in second frame if } N_{first} + TGL > 15 \end{cases}$$

N_{first} and TGL are defined in subclause 4.4.

In compressed mode by spreading factor reduction, $N_{data,j}^{cm} = 2N_{data,j} - 2N_{TGL}$, where $N_{TGL} = \frac{15 - N_{tr}}{15} N_{data,j}$

If $\Delta N_{ij} = 0$ then the output data of the rate matching is the same as the input data and the rate matching algorithm of subclause 4.2.7.5 does not need to be executed.

If $\Delta N_{ij} \neq 0$ the parameters listed in subclauses 4.2.7.1.2.1 and 4.2.7.1.2.2 shall be used for determining e_{int} , e_{plus} , and e_{minus} (regardless if the radio frame is compressed or not).

4.2.7.1.2.1 Uncoded and convolutionally encoded TrCHs

$R = \Delta N_{ij} \bmod N_{ij}$ -- note: in this context $\Delta N_{ij} \bmod N_{ij}$ is in the range of 0 to $N_{ij}-1$ i.e. $-1 \bmod 10 = 9$.

if $R \neq 0$ and $2R \leq N_{ij}$

then $q = \lceil N_{ij} / R \rceil$

else

$q = \lceil N_{ij} / (R - N_{ij}) \rceil$

endif

3GPP

Release 1999

27

3G TS 25.212 V3.2.0 (2000-03)

-- note: q is a signed quantity.

if q is even

then $q' = q + \gcd(|q|, F_i)/F_i$ -- where $\gcd(|q|, F_i)$ means greatest common divisor of $|q|$ and F_i

-- note that q' is not an integer, but a multiple of $1/8$

else

$q' = q$

endif

for $x = 0$ to $F_i - 1$

$S(I_F(|\lfloor x \cdot q' \rfloor| \bmod F_i)) = (|\lfloor x \cdot q' \rfloor| \bmod F_i)$

end for

$\Delta N_i = \Delta N_{ij}$

$a = 2$

For each radio frame, the rate-matching pattern is calculated with the algorithm in subclause 4.2.7.5, where :

$X_i = N_{ij}$, and

$e_{ini} = (a \cdot S(n_i) \cdot |\Delta N_i| + 1) \bmod (a \cdot N_{ij})$.

$e_{plus} = a \cdot N_{ij}$

$e_{minus} = a \cdot |\Delta N_i|$

puncturing for $\Delta N < 0$, repetition otherwise.

4.2.7.1.2.2 Turbo encoded TrCHs

If repetition is to be performed on turbo encoded TrCHs, i.e. $\Delta N_{ij} > 0$, the parameters in subclause 4.2.7.1.2.1 are used.

If puncturing is to be performed, the parameters below shall be used. Index b is used to indicate systematic ($b=1$), 1st parity ($b=2$), and 2nd parity bit ($b=3$).

$a=2$ when $b=2$

$a=1$ when $b=3$

$$\Delta N_i = \begin{cases} \lfloor \Delta N_{i,j} / 2 \rfloor, & b = 2 \\ \lfloor \Delta N_{i,j} / 2 \rfloor, & b = 3 \end{cases}$$

If ΔN_i is calculated as 0 for $b=2$ or $b=3$, then the following procedure and the rate matching algorithm of subclause 4.2.7.5 don't need to be performed for the corresponding parity bit stream.

$X_i = \lfloor N_{ij} / 3 \rfloor$,

$q = \lfloor X_i / \Delta N_i \rfloor$

if ($q \leq 2$)

for $x=0$ to $F_i - 1$

$S[I_F((3x+b-1) \bmod F_i)] = x \bmod 2$;

end for

else

3GPP

Release 1999

28

3G TS 25.212 V3.2.0 (2000-03)

```

    if q is even
    then q' = q - gcd(q, Fi) / Fi -- where gcd(q, Fi) means greatest common divisor of q and Fi
        -- note that q' is not an integer, but a multiple of 1/8
    else q' = q
    endif
    for x=0 to Fi - 1
        r = ⌈ x * q' ⌉ mod Fi;
        S[(IF[(3r+b-1) mod Fi])] = ⌈ x * q' ⌉ div Fi;
    endfor
endif

```

For each radio frame, the rate-matching pattern is calculated with the algorithm in subclause 4.2.7.5, where:

X_i is as above:

$$e_{ini} = (a \cdot S(n_i) \cdot |\Delta N_i| + X_i) \bmod (a \cdot X_i), \text{ if } e_{ini} = 0 \text{ then } e_{ini} = a \cdot X_i.$$

$$e_{plus} = a \cdot X_i$$

$$e_{minus} = a \cdot |\Delta N_i|$$

4.2.7.2 Determination of rate matching parameters in downlink

For downlink $N_{data,j}$ does not depend on the transport format combination j . $N_{data,*}$ is given by the channelization code(s) assigned by higher layers. Denote the number of physical channels used for the CCTrCH by P . $N_{data,*}$ is the number of bits available to the CCTrCH in one radio frame and defined as $N_{data,*} = P(15N_{data1} + 15N_{data2})$, where N_{data1} and N_{data2} are defined in [2]. Note that contrary to the uplink, the same rate matching patterns are used in normal and compressed mode by spreading factor reduction or higher layer scheduling.

In the following, the total amount of puncturing or repetition for the TTI is calculated.

Additional calculations for compressed mode by puncturing in case of fixed positions are performed to determine this total amount of rate matching needed.

For compressed mode by puncturing, in TTIs where some compressed radio frames occur, the puncturing is increased or the repetition is decreased compared to what is calculated according to the rate matching parameters provided by higher layers. This allows to create room for later insertion of marked p-bits, which will identify the positions of the gaps in the compressed radio frames.

The amount of additional puncturing corresponds to the number of bits to create the gap in the TTI for TrCh_i. In case of fixed positions, it is calculated in addition to the amount of rate matching indicated by higher layers. It is noted $Np^{TTI,m}_{l,max}$.

In fixed positions case, to obtain the total rate matching $\Delta N^{TTI,cm,m}_{l,max}$ to be performed on the TTI m , $Np^{TTI,m}_{l,max}$ is sub-stracted from $\Delta N^{TTI,m}_{l,max}$ (calculated based on higher layers RM parameters as for normal rate matching). This allows to create room for the $Np^{TTI,m}_{l,max}$ bits p to be inserted later. If the result is null, i.e. the amount of repetition matches exactly the amount of additional puncturing needed, then no rate matching is necessary.

In case of compressed mode by puncturing and fixed positions, for some calculations, $N'_{data,*}$ is used for radio frames with gap instead of $N_{data,*}$, where $N'_{data,*} = P(15N'_{data1} + 15N'_{data2})$. N'_{data1} and N'_{data2} are the number of bits in the data fields of the slot format used for the current compressed mode, i.e. slot format A or B as defined in [2] corresponding to the Spreading Factor and the number of transmitted slots in use.

Release 1999

29

3G TS 25.212 V3.2.0 (2000-03)

The number of bits corresponding to the gap for TrCh i , in each radio frame of its TTI is calculated using the number of bits to remove on each Physical Channel $N_{TGL}[k]$, where k is the radio frame number in the TTI.

For each radio frame k of the TTI, $N_{TGL}[k]$ is given by the relation:

$$N_{TGL} = \begin{cases} \frac{TGL}{15} N'_{data,*}, & \text{if } N_{first} + TGL \leq 15 \\ \frac{15 - N_{first}}{15} N'_{data,*}, & \text{in first radio frame of the gap if } N_{first} + TGL > 15 \\ \frac{TGL - (15 - N_{first})}{15} N'_{data,*}, & \text{in second radio frame of the gap if } N_{first} + TGL > 15 \end{cases}$$

N_{first} and TGL are defined in subclause 4.4.

Note that $N_{TGL}[k] = 0$ if radio frame k is not compressed.

4.2.7.2.1 Determination of rate matching parameters for fixed positions of TrCHs

4.2.7.2.1.1 Calculation of ΔN_{max} for normal mode and compressed mode by higher layer scheduling and spreading factor reduction

First an intermediate calculation variable $N_{i,*}$ is calculated for all transport channels i by the following formula:

$$N_{i,*} = \frac{1}{F_i} \cdot \max_{l \in TFS(i)} N_{i,l}^{TTI}$$

The computation of the $\Delta N_{i,l}^{TTI}$ parameters is then performed in for all TrCH i and all TF l by the following formula, where $\Delta N_{i,*}$ is derived from $N_{i,*}$ by the formula given at subclause 4.2.7:

$$\Delta N_{max} = F_i \cdot \Delta N_{i,*}$$

If $\Delta N_{max} = 0$ then, for TrCH i , the output data of the rate matching is the same as the input data and the rate matching algorithm of subclause 4.2.7.5 does not need to be executed. In this case we have :

$$\forall l \in TFS(i) \Delta N_{i,l}^{TTI} = 0$$

If $\Delta N_{max} \neq 0$ the parameters listed in subclauses 4.2.7.2.1.3 and 4.2.7.2.1.4 shall be used for determining e_{plus} and e_{minus} .

4.2.7.2.1.2 Calculations for compressed mode by puncturing

Calculations of $\Delta N_{i,max}^{TTI,m}$ for all TTI m within largest TTI, for all TrCh i

First an intermediate calculation variable $N^n_{i,*}$ is calculated for all transport channels i and all frames n in TTI m within the largest TTI, using the same formula as for normal mode above by replacing $N_{i,l}^{TTI}$ by $N_{i,l}^{TTI,m}$, the number of bits in TTI m .

The computation of the $\Delta N_{i,max}^{TTI,m}$ parameters is then performed for all TrCH i by the following formula,

$$\Delta N_{i,max}^{TTI,m} = \sum_{n=0}^{n=FI} \Delta N^n_{i,*}$$

3GPP

Release 1999

30

3G TS 25.212 V3.2.0 (2000-03)

where all $\Delta N_{i,n}^*$ are derived from $N_{i,n}^*$ for all TrCh i and all frames n in TTI m , from the formula given at subclause 4.2.7 using $N_{data,n}^*$ for the non compressed frames of TTI m and using $N_{data,n}^*$ instead of $N_{data,n}^*$, for the compressed frames of TTI m .

Calculations of $Np_{i,max}^{TTI,m}$ and $Np_{i,max}^{TTI,m}$

Let $Np_{i,max}^{TTI,m}$ be the number of bits to eliminate on TrCh i to create the gap for compressed mode, in each radio frame k of the TTI, calculated for the Transport Format Combination of TrCh i , in which the number of bits of TrCh i is at its maximum.

$Np_{i,max}^{TTI,m}$ is calculated for each radio frame k of the TTI in the following way.

Intermediate variables Z_i for $i = 1$ to I are calculated using the formula (1) in 4.2.7, by replacing $N_{data,n}^*$ by $N_{TGL}[k]$.

Then $Np_{i,max}^{TTI,m} = (Z_i - Z_{i-1})$ for $i = 1$ to I

The total number of bits $Np_{i,max}^{TTI,m}$ corresponding to the gaps for compressed mode for TrCh i in the TTI is calculated as:

$$Np_{i,max}^{TTI,m} = \sum_{i=0}^{I-1} Np_{i,max}^{TTI,m}$$

If $\Delta N_{max} = Np_{i,max}^{TTI,m}$, then, for TrCH i , the output data of the rate matching is the same as the input data and the rate matching algorithm of subclause 4.2.7.5 does not need to be executed. If $\Delta N_{max} \neq Np_{i,max}^{TTI,m}$, then, for TrCH i , the rate matching algorithm of subclause 4.2.7.5 needs to be executed.

$$\Delta N_{i,max}^{TTI,cm,m} = \Delta N_{i,max}^{TTI,m} - Np_{i,max}^{TTI,m}$$

4.2.7.2.1.3 Determination of rate matching parameters for uncoded and convolutionally encoded TrCHs

$$\Delta N_i = \Delta N_{max}$$

For compressed mode by puncturing, ΔN_i is defined as: $\Delta N_i = \Delta N_{i,max}^{TTI,cm,m}$, instead of the previous relation.

$$\alpha = 2$$

$$N_{max} = \max_{i \in TS(i)} N_{il}^{TTI}$$

For each transmission time interval of TrCH i with TF I , the rate-matching pattern is calculated with the algorithm in subclause 4.2.7.5. The following parameters are used as input:

$$X_i = N_{il}^{TTI}$$

$$e_{int} = 1$$

$$e_{punc} = \alpha \cdot N_{max}$$

$$e_{min us} = \alpha \cdot |\Delta N_i|$$

Puncturing if $\Delta N_i < 0$, repetition otherwise. The values of $\Delta N_{i,l}^{TTI}$ may be computed by counting repetitions or puncturing when the algorithm of subclause 4.2.7.5 is run. The resulting values of $\Delta N_{i,l}^{TTI}$ can be represented with following expression.

$$\Delta N_{i,l}^{TTI} = \left\lceil \frac{|\Delta N_{max}| \times X_i}{N_{max}} \right\rceil \times \text{sgn}(\Delta N_{max})$$

Release 1999

31

3G TS 25.212 V3.2.0 (2000-03)

4.2.7.2.1.4

Determination of rate matching parameters for Turbo encoded TrCHs

If repetition is to be performed on turbo encoded TrCHs, i.e. $\Delta N_{max} > 0$, the parameters in subclause 4.2.7.2.1.3 are used.

If puncturing is to be performed, the parameters below shall be used. Index b is used to indicate systematic ($b=1$), 1st parity ($b=2$), and 2nd parity bit ($b=3$).

$$a=2 \text{ when } b=2$$

$$a=1 \text{ when } b=3$$

The bits indicated by $b=1$ shall not be punctured.

$$\Delta N_i = \begin{cases} \lfloor \Delta N_{max} / 2 \rfloor, & b=2 \\ \lceil \Delta N_{max} / 2 \rceil, & b=3 \end{cases}$$

In Compressed Mode by puncturing, the following relations are used instead of the previous ones:

$$\Delta N_i = \lfloor \Delta N_{i,max}^{TTI,cm,m} / 2 \rfloor, \quad b=2$$

$$\Delta N_i = \lceil \Delta N_{i,max}^{TTI,cm,m} / 2 \rceil, \quad b=3$$

$$N_{max} = \max_{i \in TFS(i)} (N_i^{TTI} / 3)$$

For each transmission time interval of TrCH i with TF I , the rate-matching pattern is calculated with the algorithm in subclause 4.2.7.5. The following parameters are used as input:

$$X_i = N_i^{TTI} / 3$$

$$e_{int} = N_{max}$$

$$e_{plus} = a \cdot N_{max}$$

$$e_{minus} = a \cdot |\Delta N_i|$$

The values of $\Delta N_{i,j}^{TTI}$ may be computed by counting puncturing when the algorithm of subclause 4.2.7.5 is run. The resulting values of $\Delta N_{i,j}^{TTI}$ can be represented with following expression.

$$\Delta N_{i,j}^{TTI} = \left\lfloor \frac{\lfloor \Delta N_{max} / 2 \rfloor \times X_i}{N_{max}} + 0.5 \right\rfloor - \left\lfloor \frac{\lceil \Delta N_{max} / 2 \rceil \times X_i}{N_{max}} \right\rfloor$$

In the above equation, the first term of the right hand side represents the amount of puncturing for $b=2$ and the second term represents the amount of puncturing for $b=3$.

4.2.7.2.2

Determination of rate matching parameters for flexible positions of TrCHs

4.2.7.2.2.1

Calculations for normal mode, compressed mode by higher layer scheduling, and compressed mode by spreading factor reduction

First an intermediate calculation variable N_{ij} is calculated for all transport channels i and all transport format combinations j by the following formula:

3GPP

Release 1999

32

3G TS 25.212 V3.2.0 (2000-03)

$$N_{i,j} = \frac{1}{F_i} \cdot N_{i,TF_i(j)}^{TM}$$

Then rate matching ratios RF_i are calculated for each the transport channel i in order to minimise the number of DTX bits when the bit rate of the CCTrCH is maximum. The RF_i ratios are defined by the following formula:

$$RF_i = \frac{N_{data,*}}{\max_{j \in TFCS} \sum_{i=1}^{I-1} (RM_i \cdot N_{i,j})} \cdot RM_i$$

The computation of $\Delta N_{i,j}^{TM}$ parameters is then performed in two phases. In a first phase, tentative temporary values of $\Delta N_{i,j}^{TM}$ are computed, and in the second phase they are checked and corrected. The first phase, by use of the RF_i ratios, ensures that the number of DTX indication bits inserted is minimum when the CCTrCH bit rate is maximum, but it does not ensure that the maximum CCTrCH bit rate is not greater than $N_{data,*}$ per 10ms. The latter condition is ensured through the checking and possible corrections carried out in the second phase.

At the end of the second phase, the latest value of $\Delta N_{i,j}^{TM}$ is the definitive value.

The first phase defines the tentative temporary $\Delta N_{i,l}^{TM}$ for all transport channel i and any of its transport format l by use of the following formula:

$$\Delta N_{i,l}^{TM} = F_i \cdot \left[\frac{RF_i \cdot N_{i,l}^{TM}}{F_i} \right] - N_{i,l}^{TM} = F_i \cdot \left[\frac{N_{data,*} \cdot RM_i \cdot N_{i,l}^{TM}}{F_i \cdot \max_{j \in TFCS} \sum_{i=1}^{I-1} (RM_i \cdot N_{i,j})} \right] - N_{i,l}^{TM}$$

The second phase is defined by the following algorithm:

for all j in $TFCS$ do -- for all TFC

$$D = \sum_{i=1}^{I-1} \frac{N_{i,TF_i(j)}^{TM} + \Delta N_{i,TF_i(j)}^{TM}}{F_i} \quad \text{-- CCTrCH bit rate (bits per 10ms) for TFC } l$$

if $D > N_{data,*}$ then

for $l = 1$ to L do -- for all TrCH

$$\Delta N = F_i \cdot \Delta N_{i,l} \quad \text{-- } \Delta N_{i,l} \text{ is derived from } N_{i,l} \text{ by the formula given at subclause 4.2.7.}$$

if $\Delta N_{i,TF_i(j)}^{TM} > \Delta N$ then

$$\Delta N_{i,TF_i(j)}^{TM} = \Delta N$$

end-if

end-for

end-if

end-for

NOTE: The order in which the transport format combinations are checked does not change the final result.

If $\Delta N_{i,l}^{TM} = 0$ then, for TrCH i at TF l , the output data of the rate matching is the same as the input data and the rate matching algorithm of subclause 4.2.7.5 does not need to be executed.

3GPP

Release 1999

33

3G TS 25.212 V3.2.0 (2000-03)

If $\Delta N_{i,l}^{TTI} \neq 0$ the parameters listed in subclauses 4.2.7.2.2.2 and 4.2.7.2.2.3 shall be used for determining e_{ini} , e_{plus} , and e_{minus} .

4.2.7.2.2.2 Determination of rate matching parameters for uncoded and convolutionally encoded TrCHs

$$\Delta N_i = \Delta N_{il}^{TTI}$$

$$a=2$$

For each transmission time interval of TrCH i with TF l , the rate-matching pattern is calculated with the algorithm in subclause 4.2.7.5. The following parameters are used as input:

$$X_i = N_{il}^{TTI}$$

$$e_{ini} = 1$$

$$e_{plus} = a \cdot N_{il}^{TTI}$$

$$e_{minus} = a \cdot |\Delta N_i|$$

puncturing for $\Delta N_i < 0$, repetition otherwise.

4.2.7.2.2.3 Determination of rate matching parameters for Turbo encoded TrCHs

If repetition is to be performed on turbo encoded TrCHs, i.e. $\Delta N_{il}^{TTI} > 0$, the parameters in subclause 4.2.7.2.2.2 are used.

If puncturing is to be performed, the parameters below shall be used. Index b is used to indicate systematic ($b=1$), 1st parity ($b=2$), and 2nd parity bit ($b=3$).

$$a=2 \text{ when } b=2$$

$$a=1 \text{ when } b=3$$

The bits indicated by $b=1$ shall not be punctured.

$$\Delta N_i = \begin{cases} \lfloor \Delta N_{il}^{TTI} / 2 \rfloor, & b=2 \\ \lfloor \Delta N_{il}^{TTI} / 2 \rfloor, & b=3 \end{cases}$$

For each transmission time interval of TrCH i with TF l , the rate-matching pattern is calculated with the algorithm in subclause 4.2.7.5. The following parameters are used as input:

$$X_i = N_{il}^{TTI} / 3,$$

$$e_{ini} = X_i,$$

$$e_{plus} = a \cdot X_i$$

$$e_{minus} = a \cdot |\Delta N_i|$$

4.2.7.3 Bit separation and collection in uplink

The systematic bits (excluding bits for trellis termination) of turbo encoded TrCHs shall not be punctured. The systematic bit, first parity bit, and second parity bit in the bit sequence input to the rate matching block are therefore separated from each other. Puncturing is only applied to the parity bits and systematic bits used for trellis termination.

3GPP

Release 1999

34

3G TS 25.212 V3.2.0 (2000-03)

The bit separation function is transparent for uncoded TrCHs, convolutionally encoded TrCHs, and for turbo encoded TrCHs with repetition. The bit separation and bit collection are illustrated in figures 5 and 6.




Figure 5: Puncturing of turbo encoded TrCHs in uplink




Figure 6: Rate matching for uncoded TrCHs, convolutionally encoded TrCHs, and for turbo encoded TrCHs with repetition in uplink

The bit separation is dependent on the 1st interleaving and offsets are used to define the separation for different TTIs. The offsets α_b for the systematic ($b=1$) and parity bits ($b \in \{2, 3\}$) are listed in table 4.

Table 4: TTI dependent offset needed for bit separation

TTI (ms)	α_1	α_2	α_3
10, 40	0	1	2
20, 80	0	2	1

Release 1999

35

3G TS 25.212 V3.2.0 (2000-03)

The bit separation is different for different radio frames in the TTI. A second offset is therefore needed. The radio frame number for TrCH i is denoted by n_i , and the offset by β_{n_i} .

Table 5: Radio frame dependent offset needed for bit separation

TTI (ms)	β_0	β_1	β_2	β_3	β_4	β_5	β_6	β_7
10	0	NA	NA	NA	NA	NA	NA	NA
20	0	1	NA	NA	NA	NA	NA	NA
40	0	1	2	0	NA	NA	NA	NA
80	0	1	2	0	1	2	0	1

4.2.7.3.1 Bit separation

The bits input to the rate matching are denoted by $e_{i1}, e_{i2}, e_{i3}, \dots, e_{iN_i}$, where i is the TrCH number and N_i is the number of bits input to the rate matching block. Note that the transport format combination number j for simplicity has been left out in the bit numbering, i.e. $N_i = N_{ij}$. The bits after separation are denoted by $x_{bi1}, x_{bi2}, x_{bi3}, \dots, x_{biX_i}$. For turbo encoded TrCHs with puncturing, b indicates systematic, first parity, or second parity bit. For all other cases b is defined to be 1. X_i is the number of bits in each separated bit sequence. The relation between e_{ik} and x_{bik} is given below.

For turbo encoded TrCHs with puncturing:

$$x_{1,i,k} = e_{i,3(k-1)+1+(\alpha_1+\beta_{n_i}) \bmod 3} \quad k = 1, 2, 3, \dots, X_i \quad X_i = \lfloor N_i/3 \rfloor$$

$$x_{1,i,\lfloor N_i/3 \rfloor + k} = e_{i,3\lfloor N_i/3 \rfloor + k} \quad k = 1, \dots, N_i \bmod 3 \quad \text{Note: When } (N_i \bmod 3) = 0 \text{ this row is not needed.}$$

$$x_{2,i,k} = e_{i,3(k-1)+1+(\alpha_2+\beta_{n_i}) \bmod 3} \quad k = 1, 2, 3, \dots, X_i \quad X_i = \lfloor N_i/3 \rfloor$$

$$x_{3,i,k} = e_{i,3(k-1)+1+(\alpha_3+\beta_{n_i}) \bmod 3} \quad k = 1, 2, 3, \dots, X_i \quad X_i = \lfloor N_i/3 \rfloor$$

For uncoded TrCHs, convolutionally encoded TrCHs, and turbo encoded TrCHs with repetition:

$$x_{1,i,k} = e_{i,k} \quad k = 1, 2, 3, \dots, X_i \quad X_i = N_i$$

4.2.7.3.2 Bit collection

The bits x_{bik} are input to the rate matching algorithm described in subclause 4.2.7.5. The bits output from the rate matching algorithm are denoted $y_{bi1}, y_{bi2}, y_{bi3}, \dots, y_{biY_i}$.

Bit collection is the inverse function of the separation. The bits after collection are denoted by $z_{bi1}, z_{bi2}, z_{bi3}, \dots, z_{biY_i}$. After bit collection, the bits indicated as punctured are removed and the bits are then denoted by $f_{i1}, f_{i2}, f_{i3}, \dots, f_{iY_i}$, where i is the TrCH number and $Y_i = N_i + \Delta N_{ij}$. The relations between y_{bik} , z_{bik} , and f_{ik} are given below.

For turbo encoded TrCHs with puncturing ($Y_i = X_i$):

$$z_{1,i,3(k-1)+1+(\alpha_1+\beta_{n_i}) \bmod 3} = y_{1,i,k} \quad k = 1, 2, 3, \dots, Y_i$$

$$z_{1,i,\lfloor N_i/3 \rfloor + k} = y_{1,i,\lfloor N_i/3 \rfloor + k} \quad k = 1, \dots, N_i \bmod 3 \quad \text{Note: When } (N_i \bmod 3) = 0 \text{ this row is not needed.}$$

$$z_{2,i,3(k-1)+1+(\alpha_2+\beta_{n_i}) \bmod 3} = y_{2,i,k} \quad k = 1, 2, 3, \dots, Y_i$$

$$z_{3,i,3(k-1)+1+(\alpha_3+\beta_{n_i}) \bmod 3} = y_{3,i,k} \quad k = 1, 2, 3, \dots, Y_i$$

3GPP

Release 1999

36

3G TS 25.212 V3.2.0 (2000-03)

After the bit collection, bits $z_{i,k}$ with value δ , where $\delta \in \{0, 1\}$, are removed from the bit sequence. Bit $f_{i,1}$ corresponds to the bit $z_{i,k}$ with smallest index k after puncturing, bit $f_{i,2}$ corresponds to the bit $z_{i,k}$ with second smallest index k after puncturing, and so on.

For uncoded TrCHs, convolutionally encoded TrCHs, and turbo encoded TrCHs with repetition:

$$z_{i,k} = y_{i,k} \quad k = 1, 2, 3, \dots, Y_i$$

When repetition is used, $f_{i,k} = z_{i,k}$ and $Y_i = V_i$.

When puncturing is used, $Y_i = X_i$ and bits $z_{i,k}$ with value δ , where $\delta \in \{0, 1\}$, are removed from the bit sequence. Bit $f_{i,1}$ corresponds to the bit $z_{i,k}$ with smallest index k after puncturing, bit $f_{i,2}$ corresponds to the bit $z_{i,k}$ with second smallest index k after puncturing, and so on.

4.2.7.4 Bit separation and collection in downlink

The systematic bits (excluding bits for trellis termination) of turbo encoded TrCHs shall not be punctured. The systematic bit, first parity bit, and second parity bit in the bit sequence input to the rate matching block are therefore separated from each other. Puncturing is only applied to the parity bits and systematic bits used for trellis termination.

The bit separation function is transparent for uncoded TrCHs, convolutionally encoded TrCHs, and for turbo encoded TrCHs with repetition. The bit separation and bit collection are illustrated in figures 7 and 8.




Figure 7: Puncturing of turbo encoded TrCHs in downlink

Release 1999

37

3G TS 25.212 V3.2.0 (2000-03)




Figure 8: Rate matching for uncoded TrCHs, convolutionally encoded TrCHs, and for turbo encoded TrCHs with repetition in downlink

4.2.7.4.1 Bit separation

The bits input to the rate matching are denoted by $c_{i1}, c_{i2}, c_{i3}, \dots, c_{iE_i}$, where i is the TrCH number and E_i is the number of bits input to the rate matching block. Note that E_i is a multiple of 3 for turbo encoded TrCHs and that the transport format combination number j for simplicity has been left out in the bit numbering, i.e. $E_i = N_{ij}$. The bits after separation are denoted by $x_{b1}, x_{b2}, x_{b3}, \dots, x_{bX_i}$. For turbo encoded TrCHs with puncturing, b indicates systematic, first parity, or second parity bit. For all other cases b is defined to be 1. X_i is the number of bits in each separated bit sequence. The relation between c_{ik} and x_{bik} is given below.

For turbo encoded TrCHs with puncturing:

$$\begin{aligned} x_{1,i,k} &= c_{i,3(k-1)+1} & k &= 1, 2, 3, \dots, X_i & X_i &= E_i / 3 \\ x_{2,i,k} &= c_{i,3(k-1)+2} & k &= 1, 2, 3, \dots, X_i & X_i &= E_i / 3 \\ x_{3,i,k} &= c_{i,3(k-1)+3} & k &= 1, 2, 3, \dots, X_i & X_i &= E_i / 3 \end{aligned}$$

For uncoded TrCHs, convolutionally encoded TrCHs, and turbo encoded TrCHs with repetition:

$$x_{1,i,k} = c_{i,k} \quad k = 1, 2, 3, \dots, X_i \quad X_i = E_i$$

4.2.7.4.2 Bit collection

The bits x_{bik} are input to the rate matching algorithm described in subclause 4.2.7.5. The bits output from the rate matching algorithm are denoted $y_{b1}, y_{b2}, y_{b3}, \dots, y_{bX_i}$.

Bit collection is the inverse function of the separation. The bits after collection are denoted by $z_{b1}, z_{b2}, z_{b3}, \dots, z_{bX_i}$. After bit collection, the bits indicated as punctured are removed and the bits are then denoted by $g_{i1}, g_{i2}, g_{i3}, \dots, g_{iG_i}$, where i is the TrCH number and $G_i = N_{ij} + \Delta N_{ij}$. The relations between y_{bik} , z_{bik} , and g_{ik} are given below.

For turbo encoded TrCHs with puncturing ($Y_i = X_i$):

$$\begin{aligned} z_{1,i,3(k-1)+1} &= y_{1,i,k} & k &= 1, 2, 3, \dots, Y_i \\ z_{1,i,3(k-1)+2} &= y_{2,i,k} & k &= 1, 2, 3, \dots, Y_i \end{aligned}$$

3GPP

Release 1999

38

3G TS 25.212 V3.2.0 (2000-03)

$$z_{i,3(k-1)+3} = y_{3j,k} \quad k = 1, 2, 3, \dots, Y_i$$

After the bit collection, bits $z_{i,k}$ with value δ , where $\delta \in \{0, 1\}$, are removed from the bit sequence. Bit $g_{i,1}$ corresponds to the bit $z_{i,k}$ with smallest index k after puncturing, bit $g_{i,2}$ corresponds to the bit $z_{i,k}$ with second smallest index k after puncturing, and so on.

For uncoded TrCHs, convolutionally encoded TrCHs, and turbo encoded TrCHs with repetition:

$$z_{i,k} = y_{1j,k} \quad k = 1, 2, 3, \dots, Y_i$$

When repetition is used, $g_{i,k} = z_{i,k}$ and $Y_i = G_i$.

When puncturing is used, $Y_i = X_i$ and bits $z_{i,k}$ with value δ , where $\delta \in \{0, 1\}$, are removed from the bit sequence. Bit $g_{i,1}$ corresponds to the bit $z_{i,k}$ with smallest index k after puncturing, bit $g_{i,2}$ corresponds to the bit $z_{i,k}$ with second smallest index k after puncturing, and so on.

4.2.7.5 Rate matching pattern determination

Denote the bits before rate matching by:

$x_{i1}, x_{i2}, x_{i3}, \dots, x_{iX_i}$, where i is the TrCH number and the sequence is defined in 4.2.7.3 for uplink or in 4.2.7.4 for downlink. Parameters X_i , e_{ini} , e_{plus} , and e_{minus} are given in 4.2.7.1 for uplink or in 4.2.7.2 for downlink.

The rate matching rule is as follows:

if puncturing is to be performed

$e = e_{ini}$ -- initial error between current and desired puncturing ratio

$m = 1$ -- index of current bit

do while $m \leq X_i$

$e = e - e_{minus}$ -- update error

if $e \leq 0$ then -- check if bit number m should be punctured

set bit $x_{i,m}$ to δ where $\delta \in \{0, 1\}$

$e = e + e_{plus}$ -- update error

end if

$m = m + 1$ -- next bit

end do

else

$e = e_{ini}$ -- initial error between current and desired puncturing ratio

$m = 1$ -- index of current bit

do while $m \leq X_i$

$e = e - e_{minus}$ -- update error

do while $e \leq 0$ -- check if bit number m should be repeated

repeat bit $x_{i,m}$

$e = e + e_{plus}$ -- update error

end do

3GPP

Release 1999

39

3G TS 25.212 V3.2.0 (2000-03)

$$m = m + 1 \quad \text{--- next bit}$$

end do

end if

A repeated bit is placed directly after the original one.

4.2.8 TrCH multiplexing

Every 10 ms, one radio frame from each TrCH is delivered to the TrCH multiplexing. These radio frames are serially multiplexed into a coded composite transport channel (CCTrCH).

The bits input to the TrCH multiplexing are denoted by $f_{i1}, f_{i2}, f_{i3}, \dots, f_{iV_i}$, where i is the TrCH number and V_i is the number of bits in the radio frame of TrCH i . The number of TrCHs is denoted by I . The bits output from TrCH multiplexing are denoted by $s_1, s_2, s_3, \dots, s_S$, where S is the number of bits, i.e. $S = \sum_i V_i$. The TrCH multiplexing is defined by the following relations:

$$s_k = f_{1k} \quad k = 1, 2, \dots, V_1$$

$$s_k = f_{2,(k-V_1)} \quad k = V_1+1, V_1+2, \dots, V_1+V_2$$

$$s_k = f_{3,(k-(V_1+V_2))} \quad k = (V_1+V_2)+1, (V_1+V_2)+2, \dots, (V_1+V_2)+V_3$$

...

$$s_k = f_{I,(k-(V_1+V_2+\dots+V_{I-1}))} \quad k = (V_1+V_2+\dots+V_{I-1})+1, (V_1+V_2+\dots+V_{I-1})+2, \dots, (V_1+V_2+\dots+V_{I-1})+V_I$$

4.2.9 Insertion of discontinuous transmission (DTX) indication bits

In the downlink, DTX is used to fill up the radio frame with bits. The insertion point of DTX indication bits depends on whether fixed or flexible positions of the TrCHs in the radio frame are used. It is up to the UTRAN to decide for each CCTrCH whether fixed or flexible positions are used during the connection. DTX indication bits only indicate when the transmission should be turned off, they are not transmitted.

4.2.9.1 1st insertion of DTX indication bits

This step of inserting DTX indication bits is used only if the positions of the TrCHs in the radio frame are fixed. With fixed position scheme a fixed number of bits is reserved for each TrCH in the radio frame.

The bits from rate matching are denoted by $g_{i1}, g_{i2}, g_{i3}, \dots, g_{iG_i}$, where G_i is the number of bits in one TTI of TrCH i . Denote the number of bits in one radio frame of TrCH i by H_i . Denote D_i the number of bits output of the first DTX insertion block.

In normal or compressed mode by spreading factor reduction, H_i is constant and corresponds to the maximum number of bits from TrCH i in one radio frame for any transport format of TrCH i , and $D_i = F_i * H_i$.

In compressed mode by puncturing, additional puncturing is performed in the rate matching block. The empty positions resulting from the additional puncturing are used to insert p-bits in the first interleaving block, the DTX insertion is therefore limited to allow for later insertion of p-bits. Thus DTX bits are inserted until the total number of bits is D_i where $D_i = F_i * H_i + \Delta N_{cm,i,max}^{TTI}$, and $H_i = N_{i,s} + \Delta N_{i,s}$.

The bits output from the DTX insertion are denoted by $h_{i1}, h_{i2}, h_{i3}, \dots, h_{iD_i}$. Note that these bits are three valued. They are defined by the following relations:

$$h_{ik} = g_{ik} \quad k = 1, 2, 3, \dots, G_i$$

Release 1999

40

3G TS 25.212 V3.2.0 (2000-03)

$$h_{ik} = \delta \quad k = G_i+1, G_i+2, G_i+3, \dots, D_i$$

where DTX indication bits are denoted by δ . Here $g_{ik} \in \{0, 1\}$ and $\delta \in \{0, 1\}$.

4.2.9.2 2nd insertion of DTX indication bits

The DTX indication bits inserted in this step shall be placed at the end of the radio frame. Note that the DTX will be distributed over all slots after 2nd interleaving.

The bits input to the DTX insertion block are denoted by $s_1, s_2, s_3, \dots, s_S$, where S is the number of bits from TrCH multiplexing. The number of PhCHs is denoted by P and the number of bits in one radio frame, including DTX indication bits, for each PhCH by R .

In normal mode $R = \frac{N_{data,*}}{P} = 15N_{data1} + 15N_{data2}$, where N_{data1} and N_{data2} are defined in [2].

For compressed mode, $N'_{data,*}$ is defined as $N'_{data,*} = P(15N'_{data1} + 15N'_{data2})$. N'_{data1} and N'_{data2} are the number of bits in the data fields of the slot format used for the current compressed mode, i.e. slot format A or B as defined in [2] corresponding to the Spreading Factor and the number of transmitted slots in use.

In case of compressed mode by puncturing and fixed positions, DTX shall be inserted until $N'_{data,*}$ bits, since the exact room for the gap is already reserved thanks to the earlier insertion of the p-bits. Therefore R is defined as $R = N'_{data,*} / P$.

In compressed mode by SF reduction and by higher layer scheduling, additional DTX shall be inserted if the transmission time reduction method does not exactly create a transmission gap of the desired TGL. The number of bits available to the CCTrCH in one radio frame in compressed mode by SF reduction and by higher layer scheduling is

denoted by $N_{data,*}^{cm}$ and $R = \frac{N_{data,*}^{cm}}{P}$. The exact value of $N_{data,*}^{cm}$ is dependent on the TGL and the transmission time reduction method, which are signalled from higher layers. For transmission time reduction by SF/2 method in

compressed mode $N_{data,*}^{cm} = \frac{N'_{data,*}}{2}$, and for other methods it can be calculated as $N_{data,*}^{cm} = N'_{data,*} - N_{TGL}$. For

every transmission time reduction method $N'_{data,*} = P(15N'_{data1} + 15N'_{data2})$, where N'_{data1} and N'_{data2} are the number of bits in the data fields of a slot for slot format A or B as defined in [2]. N_{TGL} is the number of bits that are located within the transmission gap and defined as:

$$N_{TGL} = \begin{cases} \frac{TGL}{15} N'_{data,*}, & \text{if } N_{first} + TGL \leq 15 \\ \frac{15 - N_{first}}{15} N'_{data,*}, & \text{in first frame if } N_{first} + TGL > 15 \\ \frac{TGL - (15 - N_{first})}{15} N'_{data,*}, & \text{in second frame if } N_{first} + TGL > 15 \end{cases}$$

N_{first} and TGL are defined in subclause 4.4.

NOTE : In compressed mode by SF/2 method DTX is also added in physical channel mapping stage (subclause 4.2.12.2). During 2nd DTX insertion the number of CCTrCH bits is kept the same as in normal mode.

The bits output from the DTX insertion block are denoted by $w_1, w_2, w_3, \dots, w_{(PR)}$. Note that these bits are four valued in case of compressed mode by puncturing, and three valued otherwise. They are defined by the following relations:

$$w_k = s_k \quad k = 1, 2, 3, \dots, S$$

3GPP

Release 1999

41

3G TS 25.212 V3.2.0 (2000-03)

$$w_k = \delta \quad k = S+1, S+2, S+3, \dots, PR$$

where DTX indication bits are denoted by δ . Here $s_k \in \{0, 1, p\}$ and $\delta \in \{0, 1\}$.

4.2.10 Physical channel segmentation

When more than one PhCH is used, physical channel segmentation divides the bits among the different PhCHs. The bits input to the physical channel segmentation are denoted by $x_1, x_2, x_3, \dots, x_Y$, where Y is the number of bits input to the physical channel segmentation block. The number of PhCHs is denoted by P .

The bits after physical channel segmentation are denoted $u_{p1}, u_{p2}, u_{p3}, \dots, u_{pU}$, where p is PhCH number and U is the number of bits in one radio frame for each PhCH, i.e. $U = (Y - N_{TGI}) / P$ for compressed mode by puncturing, and $U = \frac{Y}{P}$ otherwise. The relation between x_k and u_{pk} is given below.

For all modes, some bits of the input flow are mapped to each code until the number of bits on the code is V . For modes other than compressed mode by puncturing, all bits of the input flow are taken to be mapped to the codes. For compressed mode by puncturing, only the bits of the input flow not corresponding to bits p are taken to be mapped to the codes, each bit p is removed to ensure creation the gap required by the compressed mode, as described below.

Bits on first PhCH after physical channel segmentation:

$$u_{1,k} = x_{i,f(k)} \quad k = 1, 2, \dots, U$$

Bits on second PhCH after physical channel segmentation:

$$u_{2,k} = x_{i,f(k+1)} \quad k = 1, 2, \dots, U$$

...

Bits on the P^{th} PhCH after physical channel segmentation:

$$u_{P,k} = x_{i,f(k+(P-1)U)} \quad k = 1, 2, \dots, U$$

where f is such that :

- for modes other than compressed mode by puncturing, $x_{i,f(k)} = x_{i,k}$, i.e. $f(k) = k$, for all k .
- for compressed mode by puncturing, bit $u_{1,1}$ corresponds to the bit $x_{i,k}$ with smallest index k when the bits p are not counted, bit $u_{1,2}$ corresponds to the bit $x_{i,k}$ with second smallest index k when the bits p are not counted, and so on for bits $u_{1,3}, \dots, u_{1,U}, u_{2,1}, u_{2,2}, \dots, u_{2,U}, \dots, u_{P,1}, u_{P,2}, \dots, u_{P,U}$,

4.2.10.1 Relation between input and output of the physical segmentation block in uplink

The bits input to the physical segmentation are denoted by $s_1, s_2, s_3, \dots, s_S$. Hence, $x_k = s_k$ and $Y = S$.

4.2.10.2 Relation between input and output of the physical segmentation block in downlink

The bits input to the physical segmentation are denoted by $w_1, w_2, w_3, \dots, w_{(PU)}$. Hence, $x_k = w_k$ and $Y = PU$.

4.2.11 2nd interleaving

The 2nd interleaving is a block interleaver with inter-column permutations. The bits input to the 2nd interleaver are denoted $u_{p1}, u_{p2}, u_{p3}, \dots, u_{pU}$, where p is PhCH number and U is the number of bits in one radio frame for one PhCH.

- (1) Set the number of columns $C_2 = 30$. The columns are numbered 0, 1, 2, ..., C_2-1 from left to right.

Release 1999

42

3G TS 25.212 V3.2.0 (2000-03)

(2) Determine the number of rows R_2 by finding minimum integer R_2 such that:

$$U \leq R_2 C_2.$$

(3) The bits input to the 2nd interleaving are written into the $R_2 \times C_2$ rectangular matrix row by row.

$$\begin{bmatrix} u_{p1} & u_{p2} & u_{p3} & \dots & u_{p30} \\ u_{p31} & u_{p32} & u_{p33} & \dots & u_{p60} \\ \vdots & \vdots & \vdots & \dots & \vdots \\ u_{p,((R_2-1)30+1)} & u_{p,((R_2-1)30+2)} & u_{p,((R_2-1)30+3)} & \dots & u_{p,(R_2 30)} \end{bmatrix}$$

(4) Perform the inter-column permutation based on the pattern $\{P_2(j)\}$ ($j = 0, 1, \dots, C_2-1$) that is shown in table 6, where $P_2(j)$ is the original column position of the j -th permuted column. After permutation of the columns, the bits are denoted by y_{pk} .

$$\begin{bmatrix} y_{p1} & y_{p,(R_2+1)} & y_{p,(2R_2+1)} & \dots & y_{p,(29R_2+1)} \\ y_{p2} & y_{p,(R_2+2)} & y_{p,(2R_2+2)} & \dots & y_{p,(29R_2+2)} \\ \vdots & \vdots & \vdots & \dots & \vdots \\ y_{pR_2} & y_{p,(2R_2)} & y_{p,(3R_2)} & \dots & y_{p,(30R_2)} \end{bmatrix}$$

(5) The output of the 2nd interleaving is the bit sequence read out column by column from the inter-column permuted $R_2 \times C_2$ matrix. The output is pruned by deleting bits that were not present in the input bit sequence, i.e. bits y_{pk} that corresponds to bits u_{pk} with $k > U$ are removed from the output. The bits after 2nd interleaving are denoted by $v_{p1}, v_{p2}, \dots, v_{pU}$, where v_{p1} corresponds to the bit y_{pk} with smallest index k after pruning, v_{p2} to the bit y_{pk} with second smallest index k after pruning, and so on.

Table 6

Number of column C_2	Inter-column permutation pattern
30	{0, 20, 10, 5, 15, 25, 3, 13, 23, 8, 18, 28, 1, 11, 21, 6, 16, 26, 4, 14, 24, 19, 9, 29, 12, 2, 7, 22, 27, 17}

4.2.12 Physical channel mapping

The PhCH for both uplink and downlink is defined in [2]. The bits input to the physical channel mapping are denoted by $v_{p1}, v_{p2}, \dots, v_{pU}$, where p is the PhCH number and U is the number of bits in one radio frame for one PhCH. The bits v_{pk} are mapped to the PhCHs so that the bits for each PhCH are transmitted over the air in ascending order with respect to k .

In compressed mode, no bits are mapped to certain slots of the PhCH(s). If $N_{first} + TGL \leq 15$, no bits are mapped to slots N_{first} to N_{last} . If $N_{first} + TGL > 15$, i.e. the transmission gap spans two consecutive radio frames, the mapping is as follows:

- In the first radio frame, no bits are mapped to slots $N_{first}, N_{first}+1, N_{first}+2, \dots, 14$.
- In the second radio frame, no bits are mapped to the slots 0, 1, 2, ..., N_{last} .

TGL , N_{first} , and N_{last} are defined in subclause 4.4.

4.2.12.1 Uplink

In uplink, the PhCHs used during a radio frame are either completely filled with bits that are transmitted over the air or not used at all. The only exception is when the UE is in compressed mode. The transmission can then be turned off during consecutive slots of the radio frame.

3GPP

Release 1999

43

3G TS 25.212 V3.2.0 (2000-03)

4.2.12.2 Downlink

In downlink, the PhCHs do not need to be completely filled with bits that are transmitted over the air. Bits $v_{pk} \in \{0, 1\}$ are not transmitted.

During compressed mode by reducing the spreading factor by 2, no bits are mapped to the DPDCH field as follows:

If $N_{frst} + TGL \leq 15$, i.e. the transmission gap spans one radio frame,

if $N_{frst} + 7 \leq 14$

no bits are mapped to slots $N_{frst}, N_{frst} + 1, N_{frst} + 2, \dots, N_{last} + (7 - TGL)$

no bits are mapped to the first $(N_{Data1} + N_{Data2})/2$ bit positions of slot $N_{last} + (8 - TGL)$

else

no bits are mapped to slots $N_{frst}, N_{frst} + 1, N_{frst} + 2, \dots, 14$

no bits are mapped to slots $N_{frst} - 1, N_{frst} - 2, N_{frst} - 3, \dots, N_{frst} - (7 - TGL - (14 - N_{last}))$

no bits are mapped to the last $(N_{Data1} + N_{Data2})/2$ bit positions of slot $N_{frst} - (8 - TGL - (14 - N_{last}))$

end if

If $N_{frst} + TGL > 15$, i.e. the transmission gap spans two consecutive radio frames,

In the first radio frame, no bits are mapped to last $(N_{Data1} + N_{Data2})/2$ bit positions in slot 7 as well as to slots 8, 9, 10, ..., 14.

In the second radio frame, no bits are mapped to slots 0, 1, 2, ..., 6 as well as to first $(N_{Data1} + N_{Data2})/2$ bit positions in slot 7.

N_{Data1} and N_{Data2} are defined in [2].

The following rules should be used for the selection of fixed or flexible positions of the TrCHs in the radio frame:

- For TrCHs not relying on TFCI for transport format detection (blind transport format detection), the positions of the transport channels within the radio frame should be fixed. In a limited number of cases, where there are a small number of transport format combinations, it is possible to allow flexible positions.
- For TrCHs relying on TFCI for transport format detection, higher layer signal whether the positions of the transport channels should be fixed or flexible.

4.2.13 Restrictions on different types of CCTrCHs

Restrictions on the different types of CCTrCHs are described in general terms in TS 25.302[11]. In this subclause those restrictions are given with layer 1 notation.

4.2.13.1 Uplink Dedicated channel (DCH)

The maximum value of the number of TrCHs I in a CCTrCH, the maximum value of the number of transport blocks M , on each transport channel, and the maximum value of the number of DPDCHs P are given from the UE capability class.

4.2.13.2 Random Access Channel (RACH)

- There can only be one TrCH in each RACH CCTrCH, i.e. $I=1$, $S_k = f_{1k}$ and $S = V_1$.
- The maximum value of the number of transport blocks M_1 on the transport channel is given from the UE capability class.
- The transmission time interval is either 10 ms or 20 ms.
- Only one PRACH is used, i.e. $P=1$, $u_{1k} = S_k$, and $U=S$.

Release 1999

44

3G TS 25.212 V3.2.0 (2000-03)

4.2.13.3 Common Packet Channel (CPCH)

- The maximum value of the number of TrCHs I in a CCTrCH, the maximum value of the number of transport blocks M_i on each transport channel, and the maximum value of the number of DPDCHs P are given from the UE capability class.

NOTE: Only the data part of the CPCH can be mapped on multiple physical channels (this note is taken from TS 25.302).

4.2.13.4 Downlink Dedicated Channel (DCH)

The maximum value of the number of TrCHs I in a CCTrCH, the maximum value of the number of transport blocks M_i on each transport channel, and the maximum value of the number of DPDCHs P are given from the UE capability class.

4.2.13.5 Downlink Shared Channel (DSCH) associated with a DCH

- The spreading factor is indicated with the TFCI or with higher layer signalling on DCH.
- The maximum value of the number of TrCHs I in a CCTrCH, the maximum value of the number of transport blocks M_i on the transport channel and the maximum value of the number of PDSCHs P are given from the UE capability class.

4.2.13.6 Broadcast channel (BCH)

- There can only be one TrCH in the BCH CCTrCH, i.e. $I=1$, $S_k = f_{1,k}$, and $S = V_1$.
- There can only be one transport block in each transmission time interval, i.e. $M_1 = 1$.
- All transport format attributes have predefined values.
- Only one primary CCPCH is used, i.e. $P=1$.

4.2.13.7 Forward access and paging channels (FACH and PCH)

- The maximum value of the number of TrCHs I in a CCTrCH and the maximum value of the number of transport blocks M_i on each transport channel are given from the UE capability class.
- The transmission time interval for TrCHs of PCH type is always 10 ms.
- Only one secondary CCPCH is used per CCTrCH, i.e. $P=1$.

4.2.14 Multiplexing of different transport channels into one CCTrCH, and mapping of one CCTrCH onto physical channels

The following rules shall apply to the different transport channels which are part of the same CCTrCH:

- 1) Transport channels multiplexed into one CCTrCH shall have co-ordinated timings. When the TFCS of a CCTrCH is changed because one or more transport channels are added to the CCTrCH or reconfigured within the CCTrCH, or removed from the CCTrCH, the change may only be made at the start of a radio frame with CFN fulfilling the relation

$$CFN \bmod F_{\max} = 0,$$

where F_{\max} denotes the maximum number of radio frames within the transmission time intervals of all transport channels which are multiplexed into the same CCTrCH, including any transport channels i which are added, reconfigured or have been removed, and CFN denotes the connection frame number of the first radio frame of the changed CCTrCH.

After addition or reconfiguration of a transport channel i within a CCTrCH, the TTI of transport channel i may only start in radio frames with CFN fulfilling the relation:

$$CFN_i \bmod F_i = 0.$$

Release 1999

45

3G TS 25.212 V3.2.0 (2000-03)

- 2) Only transport channels with the same active set can be mapped onto the same CCTrCH.
- 3) Different CCTrCHs cannot be mapped onto the same PhCH.
- 4) One CCTrCH shall be mapped onto one or several PhCHs. These physical channels shall all have the same SF.
- 5) Dedicated Transport channels and common transport channels cannot be multiplexed into the same CCTrCH.
- 6) For the common transport channels, only the FACH and PCH may belong to the same CCTrCH.

There are hence two types of CCTrCH:

- 1) CCTrCH of dedicated type, corresponding to the result of coding and multiplexing of one or several DCHs.
- 2) CCTrCH of common type, corresponding to the result of the coding and multiplexing of a common channel, RACH in the uplink, DSCH, BCH, or FACH/PCH for the downlink.

4.2.14.1 Allowed CCTrCH combinations for one UE

4.2.14.1.1 Allowed CCTrCH combinations on the uplink

A maximum of one CCTrCH is allowed for one UE on the uplink. It can be either:

- 1) one CCTrCH of dedicated type;
- 2) one CCTrCH of common type.

4.2.14.1.2 Allowed CCTrCH combinations on the downlink

The following CCTrCH combinations for one UE are allowed:

- x CCTrCH of dedicated type + y CCTrCH of common type. The allowed combination of CCTrCHs of dedicated and common type are given from UE radio access capabilities. There can be a maximum of one CCTrCH of common type for DSCH and a maximum of one CCTrCH of common type for FACH. With one CCTrCH of common type for DSCH, there shall be at least one CCTrCH of dedicated type.

NOTE 1: There is only one DPCH in the uplink, hence one TPC bits flow on the uplink to control possibly the different DPCHs on the downlink, part of the same or several CCTrCHs.

NOTE 2: There is only one DPCH in the downlink, even with multiple CCTrCHs. With multiple CCTrCHs, the DPCH is transmitted on one of the physical channels of that CCTrCH which has the smallest SF among the multiple CCTrCHs. Thus there is only one TPC command flow and only one TFCI word in downlink even with multiple CCTrCHs.

4.3 Transport format detection

If the transport format set of a TrCH i contains more than one transport format, the transport format can be detected according to one of the following methods:

- TFCI based detection: This method is applicable when the transport format combination is signalled using the TFCI field;
- explicit blind detection: This method typically consists of detecting the TF of TrCH i by use of channel decoding and CRC check;
- guided detection: This method is applicable when there is at least one other TrCH i' , hereafter called guiding TrCH, such that:
 - the guiding TrCH has the same TTI duration as the TrCH under consideration, i.e. $T_i = T_{i'}$;
 - different TFs of the TrCH under consideration correspond to different TFs of the guiding TrCH;
 - explicit blind detection is used on the guiding TrCH.

3GPP

Release 1999

46

3G TS 25.212 V3.2.0 (2000-03)

If the transport format set for a TrCH i contains one transport format only, no transport format detection needs to be performed for this TrCH.

For uplink, blind transport format detection is a network controlled option. For downlink, the UE shall be capable of performing blind transport format detection, if certain restrictions on the configured transport channels are fulfilled.

For a DPCH associated with a PDSCH, the DPCCCH shall include TFCI.

4.3.1 Blind transport format detection

When no TFCI is available then explicit blind detection or guided detection shall be performed on all TrCHs within the CCTrCH that have more than one transport format. The UE shall only be required to support blind transport format detection if all of the following restrictions are fulfilled:

1. the number of CCTrCH bits received per radio frame is 600 or less;
2. the number of transport format combinations of the CCTrCH is 64 or less;
3. fixed positions of the transport channels is used on the CCTrCH to be detected;
4. convolutional coding is used on all explicitly detected TrCHs;
5. CRC is appended to all transport blocks on all explicitly detected TrCHs;
6. the number of explicitly detected TrCHs is 3 or less;
7. for all explicitly detected TrCHs i , the number of code blocks in one TTI (C_i) shall not exceed 1;
8. the sum of the transport format set sizes of all explicitly detected TrCHs, is 16 or less. The transport format set size is defined as the number of transport formats within the transport format set;
9. there is at least one TrCH that can be used as the guiding transport channel for all transport channels using guided detection.

Examples of blind transport format detection methods are given in annex A.

4.3.2 Transport format detection based on TFCI

If a TFCI is available, then TFCI based detection shall be applicable to all TrCHs within the CCTrCH. The TFCI informs the receiver about the transport format combination of the CCTrCHs. As soon as the TFCI is detected, the transport format combination, and hence the transport formats of the individual transport channels are known.

4.3.3 Coding of Transport-Format-Combination Indicator (TFCI)

The TFCI bits are encoded using a (32, 10) sub-code of the second order Reed-Muller code. The coding procedure is as shown in figure 9.




Figure 9: Channel coding of TFCI bits

If the TFCI consist of less than 10 bits, it is padded with zeros to 10 bits, by setting the most significant bits to zero. The length of the TFCI code word is 32 bits.

The code words of the (32,10) sub-code of second order Reed-Muller code are linear combination of 10 basis sequences. The basis sequences are as in the following table 7.

3GPP

Release 1999

47

3G TS 25.212 V3.2.0 (2000-03)

Table 7: Basis sequences for (32,10) TFCI code

i	M _{i,0}	M _{i,1}	M _{i,2}	M _{i,3}	M _{i,4}	M _{i,5}	M _{i,6}	M _{i,7}	M _{i,8}	M _{i,9}
0	1	0	0	0	0	1	0	0	0	0
1	0	1	0	0	0	1	1	0	0	0
2	1	1	0	0	0	1	0	0	0	1
3	0	0	1	0	0	1	1	0	1	1
4	1	0	1	0	0	1	0	0	0	1
5	0	1	1	0	0	1	0	0	1	0
6	1	1	1	0	0	1	0	1	0	0
7	0	0	0	1	0	1	0	1	1	0
8	1	0	0	1	0	1	1	1	1	0
9	0	1	0	1	0	1	1	0	1	1
10	1	1	0	1	0	1	0	0	1	1
11	0	0	1	1	0	1	0	1	1	0
12	1	0	1	1	0	1	0	1	0	1
13	0	1	1	1	0	1	1	0	0	1
14	1	1	1	1	0	1	1	1	1	1
15	1	0	0	0	1	1	1	1	0	0
16	0	1	0	0	1	1	1	1	0	1
17	1	1	0	0	1	1	1	0	1	0
18	0	0	1	0	1	1	0	1	1	1
19	1	0	1	0	1	1	0	1	0	1
20	0	1	1	0	1	1	0	0	1	1
21	1	1	1	0	1	1	0	1	1	1
22	0	0	0	1	1	1	0	1	0	0
23	1	0	0	1	1	1	1	1	0	1
24	0	1	0	1	1	1	1	0	0	1
25	1	1	0	1	1	1	1	0	0	1
26	0	0	1	1	1	1	0	0	1	0
27	1	0	1	1	1	1	1	1	0	0
28	0	1	1	1	1	1	1	1	1	0
29	1	1	1	1	1	1	1	1	1	1
30	0	0	0	0	0	1	0	0	0	0
31	0	0	0	0	1	1	1	0	0	0

Let's define the TFCI information bits as $a_0, a_1, a_2, a_3, a_4, a_5, a_6, a_7, a_8, a_9$ (a_0 is LSB and a_9 is MSB). The TFCI information bits shall correspond to the TFC index (expressed in unsigned binary form) defined by the RRC layer to reference the TFC of the CCTrCH in the associated DPCH radio frame.

The output code word bits b_i are given by:

$$b_i = \sum_{n=0}^9 (a_n \times M_{i,n}) \bmod 2$$

where $i=0 \dots 31$.

The output bits are denoted by $b_k, k = 0, 1, 2, \dots, 31$.

In downlink, when the SF < 128 the encoded TFCI code words are repeated yielding 8 encoded TFCI bits per slot in normal mode and 16 encoded TFCI bits per slot in compressed mode. Mapping of repeated bits to slots is explained in subclause 4.3.5.

4.3.4 Operation of Transport-Format-Combination Indicator (TFCI) in Split Mode

If one of the DCH is associated with a DSCH, the TFCI code word may be split in such a way that the code word relevant for TFCI activity indication is not transmitted from every cell. The use of such a functionality shall be indicated by higher layer signalling.

The TFCI bits are encoded using a (16, 5) bi-orthogonal (or first order Reed-Muller) code. The coding procedure is as shown in figure 10.

3GPP

Release 1999

48

3G TS 25.212 V3.2.0 (2000-03)




Figure 10: Channel coding of split mode TFCI bits

The code words of the (16,5) bi-orthogonal code are linear combinations of 5 basis sequences as defined in table 8.

Table 8: Basis sequences for (16,5) TFCI code

i	M _{1,0}	M _{1,1}	M _{1,2}	M _{1,3}	M _{1,4}
0	1	0	0	0	1
1	0	1	0	0	1
2	1	1	0	0	1
3	0	0	1	0	1
4	1	0	1	0	1
5	0	1	1	0	1
6	1	1	1	0	1
7	0	0	0	1	1
8	1	0	0	1	1
9	0	1	0	1	1
10	1	1	0	1	1
11	0	0	1	1	1
12	1	0	1	1	1
13	0	1	1	1	1
14	1	1	1	1	1
15	0	0	0	0	1

Let's define a first set of TFCI information bits as $a_{1,0}, a_{1,1}, a_{1,2}, a_{1,3}, a_{1,4}$ ($a_{1,0}$ is LSB and $a_{1,4}$ is MSB). This set of TFCI information bits shall correspond to the TFC index (expressed in unsigned binary form) defined by the RRC layer to reference the TFC of the DCH CCTrCH in the associated DPCH radio frame.

Let's define a second set of TFCI information bits as $a_{2,0}, a_{2,1}, a_{2,2}, a_{2,3}, a_{2,4}$ ($a_{2,0}$ is LSB and $a_{2,4}$ is MSB). This set of TFCI information bits shall correspond to the TFC index (expressed in unsigned binary form) defined by the RRC layer to reference the TFC of the associated DSCH CCTrCH in the corresponding PDSCH radio frame.

The output code word bits b_k are given by:

$$b_{2i} = \sum_{n=0}^4 (a_{1,n} \times M_{1,n}) \bmod 2; \quad b_{2i+1} = \sum_{n=0}^4 (a_{2,n} \times M_{1,n}) \bmod 2$$

where $i=0 \dots 15, j=0,1$.

The output bits are denoted by $b_k, k = 0, 1, 2, \dots, 31$.

4.3.5 Mapping of TFCI words

4.3.5.1 Mapping of TFCI word in non compressed mode

The bits of the code word are directly mapped to the slots of the radio frame. Within a slot the bit with lower index is transmitted before the bit with higher index. The coded bits b_k are mapped to the transmitted TFCI bits d_k according to the following formula:

$$d_k = b_{k \bmod 32}$$

3GPP

Release 1999

49

3G TS 25.212 V3.2.0 (2000-03)

For uplink physical channels regardless of the SF and downlink physical channels, if $SF \geq 128$, $k = 0, 1, 2, \dots, 29$.

NOTE: This means that bits b_{30} and b_{31} are not transmitted.

For downlink physical channels whose $SF < 128$, $k = 0, 1, 2, \dots, 119$. Note that this means that bits b_0 to b_{23} are transmitted four times and bits b_{24} to b_{31} are transmitted three times.

4.3.5.2 Mapping of TFCI in compressed mode

The mapping of the TFCI bits in compressed mode is different for uplink, downlink with $SF \geq 128$ and downlink with $SF < 128$.

4.3.5.2.1 Uplink compressed mode

For uplink compressed mode, the slot format is changed so that no TFCI bits are lost. The different slot formats in compressed mode do not match the exact number of TFCI bits for all possible TGLs. Repetition of the TFCI bits is therefore used.

Denote the number of bits available in the TFCI fields of one compressed radio frame by D and the number of bits in the TFCI field in a slot by N_{TFCI} . Denote by E the first bit to be repeated, $E = N_{first} N_{TFCI}$. If $N_{last} \neq 14$, then E corresponds to the number of the first TFCI bit in the slot directly after the TG. The following relations then define the mapping.

$$d_k = b_{k \bmod 32}$$

where $k = 0, 1, 2, \dots, \min(31, D-1)$.

If $D > 32$, the remaining positions are filled by repetition (in reversed order):

$$d_{D-k-1} = b_{(E+k) \bmod 32}$$

where $k = 0, \dots, D-33$.

4.3.5.2.2 Downlink compressed mode

For downlink compressed mode, the slot format is changed so that no TFCI bits are lost. The different slot formats in compressed mode do not match the exact number of TFCI bits for all possible TGLs. DTX is therefore used if the number of TFCI fields exceeds the number of TFCI bits. The block of fields, where DTX is used, starts on the first field after the gap. If there are fewer TFCI fields after the gap than DTX bits, the last fields before of the gap are also filled with DTX.

Denote the number of bits available in the TFCI fields of one compressed radio frame by D and the number of bits in the TFCI field in a slot by N_{TFCI} . Denote by E the first bit to be repeated.

$$E = N_{first} N_{TFCI}, \text{ if } N_{first} + TGL \leq 15, \text{ else } E = 0$$

If the transmission gap does not extend to the end of the frame then E corresponds to the number of the first TFCI bit in the slot directly after the TG. Denote the total number of TFCI bits to be transmitted by N_{tot} . If $SF \geq 128$ then $N_{tot} = 32$, else $N_{tot} = 128$. The following relations then define the mapping:

$$d_k = b_{(k \bmod 32)}$$

where $k = 0, 1, 2, \dots, \min(E, N_{tot})-1$ and, if $E < N_{tot}$,

$$d_{k+D-N_{tot}} = b_{(k \bmod 32)}$$

where $k = E, \dots, N_{tot}-1$.

DTX bits are sent on d_k where $k = \min(E, N_{tot}), \dots, \min(E, N_{tot}) + D - N_{tot} - 1$.

Release 1999

50

3G TS 25.212 V3.2.0 (2000-03)

4.4 Compressed mode

In compressed mode, TGL slots from N_{first} to N_{last} are not used for transmission of data. As illustrated in figure 11, the instantaneous transmit power is increased in the compressed frame in order to keep the quality (BER, FER, etc.) unaffected by the reduced processing gain. The amount of power increase depends on the transmission time reduction method (see subclause 4.4.3). What frames are compressed, are decided by the network. When in compressed mode, compressed frames can occur periodically, as illustrated in figure 11, or requested on demand. The rate and type of compressed frames is variable and depends on the environment and the measurement requirements.




Figure 11: Compressed mode transmission

4.4.1 Frame structure in the uplink

The frame structure for uplink compressed mode is illustrated in figure 12.




Figure 12: Frame structure in uplink compressed transmission

4.4.2 Frame structure types in the downlink

There are two different types of frame structures defined for downlink compressed mode. Type A maximises the transmission gap length and type B is optimised for power control.

- With frame structure of type A, the pilot field of the last slot in the transmission gap is transmitted. Transmission is turned off during the rest of the transmission gap (figure 13(a)).
- With frame structure of type B, the TPC field of the first slot in the transmission gap and the pilot field of the last slot in the transmission gap is transmitted. Transmission is turned off during the rest of the transmission gap (figure 13(b)).

Release 1999

51

3G TS 25.212 V3.2.0 (2000-03)




Figure 13: Frame structure types in downlink compressed transmission

4.4.3 Transmission time reduction method

When in compressed mode, the information normally transmitted during a 10 ms frame is compressed in time. The mechanisms provided for achieving this are puncturing, reduction of the spreading factor by a factor of two, and higher layer scheduling. In the downlink, all methods are supported while compressed mode by puncturing is not used in the uplink. The maximum idle length is defined to be 7 slots per one 10 ms frame. The slot formats that are used in compressed mode are listed in [2].

4.4.3.1 Compressed mode by puncturing

During compressed mode, rate matching (puncturing) is applied for creating transmission gap in one frame. The algorithm for rate matching (puncturing) as described in subclause 4.2.7 is used.

4.4.3.2 Compressed mode by reducing the spreading factor by 2

During compressed mode, the spreading factor (SF) can be reduced by 2 during one radio frame to enable the transmission of the information bits in the remaining time slots of a compressed frame.

On the downlink, UTRAN can also order the UE to use a different scrambling code in compressed mode than in normal mode. If the UE is ordered to use a different scrambling code in compressed mode, then there is a one-to-one mapping between the scrambling code used in normal mode and the one used in compressed mode, as described in TS 25.213[3] subclause 5.2.1.

4.4.3.3 Compressed mode by higher layer scheduling

Compressed mode can be obtained by higher layer scheduling. Higher layers then set restrictions so that only a subset of the allowed TFCs are used in compressed mode. The maximum number of bits that will be delivered to the physical layer during the compressed radio frame is then known and a transmission gap can be generated. Note that in the downlink, the TFCI field is expanded on the expense of the data fields and this shall be taken into account by higher layers when setting the restrictions on the TFCs. Compressed mode by higher layer scheduling shall not be used with fixed starting positions of the TrCHs in the radio frame.

4.4.4 Transmission gap position


Transmission gaps can be placed at different positions as shown in figures 14 and 15 for each purpose such as interfrequency power measurement, acquisition of control channel of other system/carrier, and actual handover operation.

When using single frame method, the transmission gap is located within the compressed frame depending on the transmission gap length (TGL) as shown in figure 14 (1). When using double frame method, the transmission gap is located on the center of two connected frames as shown in figure 14 (2).

Release 1999

52

3G TS 25.212 V3.2.0 (2000-03)

**Figure 14: Transmission gap position**

Parameters of the transmission gap positions are calculated as follows.

TGL is the number of consecutive idle slots during the compressed mode transmission gap:

$$TGL = 3, 4, 5, 7, 10, 14$$

N_{first} specifies the starting slot of the consecutive idle slots,

$$N_{first} = 0, 1, 2, 3, \dots, 14.$$

N_{last} shows the number of the final idle slot and is calculated as follows;

If $N_{first} + TGL \leq 15$, then $N_{last} = N_{first} + TGL - 1$ (in the same frame),


If $N_{first} + TGL > 15$, then $N_{last} = (N_{first} + TGL - 1) \bmod 15$ (in the next frame).

When the transmission gap spans two consecutive radio frames, N_{first} and TGL must be chosen so that at least 8 slots in each radio frame are transmitted.

Release 1999

53

3G TS 25.212 V3.2.0 (2000-03)

Figure 15: Transmission gap positions with different N_{first}

4.4.5 Parameters for downlink compressed mode

Table 9 shows the detailed parameters for each transmission gap length for the different transmission time reduction methods.

Release 1999

54

3G TS 25.212 V3.2.0 (2000-03)

Table 9: Parameters for compressed mode

TGL	Frame Type	Spreading Factor	Idle length [ms]	Transmission time Reduction method	Idle frame Combining
3	A	512 - 4	1.73-1.99	Puncturing, Spreading factor division by 2 or Higher layer scheduling	(S) (D) =(1,2) or (2,1)
	B	256 - 4	1.60-1.86		(S) (D) =(1,3), (2,2) or (3,1)
4	A	512 - 4	2.40-2.66		(S) (D) =(1,4), (2,3), (3, 2) or (4,1)
	B	256 - 4	2.27-2.53		(S) (D)=(1,6), (2,5), (3,4), (4,3), (5,2) or (6,1)
5	A	512 - 4	3.07-3.33		(D)=(3,7), (4,6), (5,5), (6,4) or (7,3)
	B	256 - 4	2.94-3.20		(D) =(7,7)
7	A	512 - 4	4.40-4.66		
	B	256 - 4	4.27-4.53		
10	A	512 - 4	6.40-6.66		
	B	256 - 4	6.27-6.53		
14	A	512 - 4	9.07-9.33		
	B	256 - 4	8.93-9.19		

(S): Single-frame method as shown in figure 14 (1).

(D): Double-frame method as shown in figure 14 (2). (x,y) indicates x: the number of idle slots in the first frame, y: the number of idle slots in the second frame.

NOTE: Compressed mode by spreading factor reduction is not supported when SF=4 is used in normal mode.

Annex A (informative): Blind transport format detection

A.1 Blind transport format detection using fixed positions

A.1.1 Blind transport format detection using received power ratio

For the dual transport format case (the possible data rates are 0 and full rate, and CRC is only transmitted for full rate), blind transport format detection using received power ratio can be used.

The transport format detection is then done using average received power ratio of DPDCH to DPCCH. Define the following:

- P_c : Received power per bit of DPCCH calculated from all pilot and TPC bits per slot over a radio frame;
- P_d : Received power per bit of DPDCH calculated from X bits per slot over a radio frame;
- X : the number of DPDCH bits per slot when transport format corresponds to full rate;
- T : Threshold of average received power ratio of DPDCH to DPCCH for transport format detection.

The decision rule can then be formulated as:

If $P_d/P_c > T$ then:

- full rate transport format detected;
- else
- zero rate transport format detected.

A.1.2 Blind transport format detection using CRC

For the multiple transport format case (the possible data rates are 0, ..., (full rate)/ r , ..., full rate, and CRC is transmitted for all transport formats), blind transport format detection using CRC can be used.

At the transmitter, the data stream with variable number of bits from higher layers is block-encoded using a cyclic redundancy check (CRC) and then convolutionally encoded. CRC parity bits are attached just after the data stream with variable number of bits as shown in figure A.1.

The receiver knows only the possible transport formats (or the possible end bit position (n_{end})) by Layer-3 negotiation. The receiver performs Viterbi-decoding on the soft decision sample sequence. The correct trellis path of the Viterbi-decoder ends at the zero state at the correct end bit position.

The blind transport format detection method using CRC traces back the surviving trellis path ending at the zero state (hypothetical trellis path) at each possible end bit position to recover the data sequence. For each recovered data sequence error-detection is performed by checking the CRC, and if there is no error, the recovered sequence is declared to be correct.

The following variable is defined:

$$s(n_{end}) = -10 \log \left((a_0(n_{end}) - a_{min}(n_{end})) / (a_{max}(n_{end}) - a_{min}(n_{end})) \right) \text{ [dB]} \quad (\text{Eq. 1})$$

where $a_{max}(n_{end})$ and $a_{min}(n_{end})$ are the maximum and minimum path-metric values among all survivors at end bit position n_{end} ; and $a_0(n_{end})$ is the path-metric value at zero state.

Release 1999

56

3G TS 25.212 V3.2.0 (2000-03)

In order to reduce the probability of false detection (this happens if the selected path is wrong but the CRC misses the error detection), a path selection threshold D is introduced. The threshold D determines whether the hypothetical trellis path connected to the zero state should be traced back or not at each end bit position n_{end} . If the hypothetical trellis path connected to the zero state that satisfies:

$$s(n_{\text{end}}) \leq D \quad (\text{Eq. 2})$$

is found, the path is traced back to recover the frame data, where D is the path selection threshold and a design parameter.

If more than one end bit positions satisfying Eq. 2 is found, the end bit position which has minimum value of $s(n_{\text{end}})$ is declared to be correct. If no path satisfying Eq. 2 is found even after all possible end bit positions have been exhausted, the received frame data is declared to be in error.

Figure A-2 shows the procedure of blind transport format detection using CRC.




Figure A.1: An example of data with variable number of bits.
Four possible transport formats, and transmitted end bit position $n_{\text{end}} = 3$

A.2 Blind transport format detection with flexible positions

In certain cases where the CCTrCH consists of multiple transport channels and a small number of transport format combinations are allowed, it is possible to allow blind transport format detection with flexible positions.

Several examples for how the blind transport format detection with flexible positions might be performed are:

- the blind transport format detection starts at a fixed position and identifies the transport format of the first present transport channel and stops. The position of the other transport channels and their transport format being derived on the basis of the allowed transport format combinations, assuming that there is a one to one relationship between the transport format combination and the transport format of the first present transport channel;
- the blind rate detection evaluates all transport format combinations and picks the most reliable one.

Release 1999

57

3G TS 25.212 V3.2.0 (2000-03)




Figure A.2: Basic processing flow of blind transport format detection

